

Synergy® metalclad

fused connection units and control switches



Finish : grey epoxy coated steel
Terminal screws captive and backed off ready for cabling
Supplied complete with close fit surface mounting back box with knockouts

Pack	Cat. Nos.	Fused connection units 13 A - 250 V~
		Conform to BS 1363 - Part 4 : 1995 Fused 13 A (fuse supplied) Fuse drawer retained by quarter turn catch, drawer padlockable in open position for safety Nominal dimensions : 86 x 86 x 43 mm
		Switched
5	7338 34	Switched, DP
5	7338 35	Switched, DP with red LED power indicator
5	7338 36	Switched, DP with cord outlet
5	7338 37	Switched, DP with cord outlet + red LED power indicator
		Unswitched
5	7338 30	Unswitched
5	7338 31	Unswitched with red LED power indicator
5	7338 32	Unswitched with cord outlet
5	7338 33	Unswitched with cord outlet + red LED power indicator

Pack	Cat. Nos.	Double pole switches 20 A - 250 V~
		Conform to BS EN 60669-1 : 2000 Nominal dimensions : 86 x 86 x 43 mm
5	7338 10	20 A DP
5	7338 14	20 A DP with cord outlet
5	7338 16	20 A DP with cord outlet + red LED power indicator
5	7338 12	20 A DP + red LED power indicator
		Cable outlet 20 A - 250 V~
		Conforms to BS 5733 : 1995 Nominal dimensions : 86 x 86 x 43 mm
5	7338 19	20 A – with terminal block and outlet gland
		Double pole switches 45 A - 250 V~
		Conform to BS EN 60669-1 : 2000 Red rocker Nominal dimensions : 146 x 86 x 43 mm
5	7338 20	45 A DP
5	7338 21	45 A DP + red LED power indicator

Surface mounting back boxes with or without knockouts
p. 60



Synergy® metalclad

TV, telephone and data sockets



7338 40



7338 41



7338 56



7338 57



7338 50



7338 95



7338 96

Finish : grey epoxy coated steel
Terminal screws captive and backed off ready for cabling
Supplied complete with close fit surface mounting back box with knockouts

Pack	Cat. Nos.	TV, radio and satellite sockets
5	7338 40	Nominal dimensions : 86 x 86 x 43 mm Screened TV – single, male Non-isolated
1	7338 41	Screened satellite – single, 'F' type

Pack	Cat. Nos.	Telephone sockets
5	7338 50 ¹	Nominal dimensions : 86 x 86 x 43 mm Single master
5	7338 51 ¹	Single secondary

Pack	Cat. Nos.	Data sockets
1	7338 56	CAT 6 compliant Rapid cable connection Nominal dimensions : 86 x 86 x 43 mm RJ45 – single
1	7338 57	RJ45 – double

Pack	Cat. Nos.	Blanking plates
5	7338 95	1 gang - 86 x 86 mm
5	7338 96	2 gang - 86 x 146 mm

Surface mounting back boxes with or without knockouts
p. 60



1 : Not suitable for use in the ROI

Download the full file at

<http://assets.kempstoncontrols.com/doc/Synergy%20Wiring%20Accessories.pdf>



KEMPSTON
CONTROLS