

Safety modules

Safety-M compact Basic module

Speed monitoring – SMC1.1

1 axis / 1 encoder system



SMC1.1 is a compact safety module of the Safety-M family with integrated drive monitoring for one axis with a safe encoder system. This standalone speed controller (basic module) can be operated without additional safe PLC.

Safety-M compact is the optimal solution for integration in existing safety circuits or for retrofitting old machines. Solutions with a safe encoder (SinCos) are supported for safe speed acquisition.



The integrated signal converter and splitter allows an easy connection of controllers, which can operate using the same encoder system. It offers in addition the possibility of issuing an analog rotational speed value, e.g. to replace tachometers or similar.

The device can be parameterized with a removable control and diagnostic display or with the PC software SafeConfig OS6.0. This way, setting and diagnostic can be performed conveniently at the office PC or totally and easily using the intuitive touchpad display in the field.

- Extensive library of pre-configured safe sensors and command devices. This allows easy parameterizing without programming.
- Complete range of speed-related safe drive monitoring functions equivalent to EN 61800-5-2 already integrated in firmware (e.g. STO, SS1, SS2, SOS, SLS, SSM, SDI).
- Integrated signal splitter for SinCos signal forwarding (optional). No complex, interference-sensitive external wiring when the controller is to use the same signals.
- The signal converter can issue the encoder signal as SinCos, TTL/RS422 or as a 4 ... 20 mA analog value.
- Snap-on installation on 35 mm C profile rail.
- 4/2 safe input lines, 8/4 safe shut-off channels, 1 safe potential-free relay open contact.
- Contact multiplication or increase of power capability by external contactors in connection with the device-internal monitoring function for external contacts (EDM).
- LED on the front side indicates operating state.
- Removable control and diagnosis display (optional).
- Free "SafeConfig" parameterization software.

Order code

8 . SMC1 . 1 X A . 241

a Encoder interface
1 = 1 x Sub-D SinCos

b Internal signal splitting
0 = without
S = with

c Analog output
A = 4 ... 20 mA

1) Safety-M compact basic module.

2) Optional control and diagnosis display – to be ordered separately (see the accessories).

Safety modules

Safety-M compact Basic module	Speed monitoring – SMC1.1	1 axis / 1 encoder system
--	----------------------------------	----------------------------------

Accessories		Order no.
Control and diagnostic display, OLED touch screen		8.SMCB.000
Programming cable, Multi-USB adapter		05.C162RK1
SafeConfig parameterization software	download at	www.kuebler.com/ safeconfig
Shield terminal for encoder cable, C profile rail		8.0000.4G06.0000
Connection technology		Order no.
Cordset, pre-assembled 2 m ¹⁾ for Sendix SIL encoders	cable, single-ended / 1 x Sub-D, 9-pin, male connector	8.0000.6V00.0002.0087
	cable, single-ended / 1 x Sub-D, 9-pin, female connector	8.0000.6V00.0002.0086
	cable with 1 x M23 / 1 x Sub-D, 9-pin, female connector	8.0000.6V00.0002.0085
	cable with 1 x M12 / 1 x Sub-D, 9-pin, female connector	8.0000.6V00.0002.0084

Further accessories can be found in accessories area of our website at: www.kuebler.com/accessories.

Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.

You will find an overview of our systems and components for Functional Safety under www.kuebler.com/safety.

Technical data

General data	
Digital input lines	4 / 2
Digital output lines	8 / 4
Safe relay outputs	1
Type of connection	pluggable screw terminals
Max. terminal cross section	1.5 mm² [AWG 15]
Drive monitoring - number of axis	1 axis
Electrical characteristics	
Power supply	24 V DC / 2.5 A
Tolerance	±20 %
Current consumption (no load)	max. 150 mA
Power consumption	max. 45 W
Fuse on power supply	max. 2.5 A, medium time-lag
Rated encoder power supply data	approx. 2V below the supply voltage / max. 200 mA
Environmental data	
Operating temperature	-20°C ... +55°C [-4°F ...+131°F]
Storage temperature	-25°C ... +70°C [-13°F ...+158°F]
Protection acc. to EN 60529	IP20
Climate class	3 acc. to DIN 50178 (non condensing)
CE compliant acc. to	EMC guideline 2014/30/EU Machinery directive 2006/42/EC Low voltage guideline 2014/35/EU RoHS guideline 2011/65/EU

Safety characteristics		
Classification	PL _e / SIL3	
System structure	2 channel (Cat. 3 / HFT = 1)	
PFH _d value	3.76 x 10 ⁻⁸ h ⁻¹	
Mission time / Proof test interval	20 years	
Reaction times	see operating instructions R60719	
Relevant standards	EN ISO 13849-1:2008 EN 62061:2005 EN 61508:2011	
EMC		
Relevant standards	EN 61000-6-2:2005 / AC:2005 EN 61000-6-4:2007 / A1:2011 EN 61326-3-2:2008	
Mechanical characteristics		
Size w x h x d	50 x 100 x 165 mm [1.97 x 3.94 x 6.50"]	
Weight	390 g [13.76 oz]	
Mounting	snap-on mounting on standard head rail	
Material	housing plastic	
Shock resistance acc. to EN 60068-2-27	300 m/s², 11 ms 170 m/s², 6 ms	
Vibration resistance acc. to EN 60068-2-6	70 m/s², 10 ... 200 Hz	
LED display		
ERROR (yellow)	steadily on flashing quickly flashing slowly	error peripheral alarm DIP 1 = OFF, factory setting DIP 3 = OFF, programming mode
ON (green)	steadily on	power on

1) Other lengths available



Safety modules

Safety-M compact Basic module		Speed monitoring – SMC1.1	1 axis / 1 encoder system
SinCos interface (IN) X6			
Type of connection	Sub-D, male connector, 9-pin		
Signal	SinCos		
Frequency	max. 500 kHz		
Signal level	1 V _{pp} (±20 %)		
Signal offset	2.5 V (±0.1 V)		
Signal termination	120 Ω		
Output voltage	2 V below the supply voltage		
Output current	max. 200 mA		
Digital inputs (IN) X10			
Type of connection	pluggable screw terminals, 5-pin		
HTL signal	incremental interface, Proximity switches or digital inputs		
Frequency	max. 250 kHz (incremental), max. 1 kHz (control signal)		
Signal level	PNP (24 V DC / 15 mA)		
Execution	complementary		
Relay outputs (OUT) X1			
Type of connection	pluggable screw terminals, 2-pin		
Wiring	two internally in line		
Type	positively driven (NO)		
Switching ability	5 ... 36 V DC		
Switching capacity	5 ... 5000 mA		
Digital switching outputs (OUT) X2			
Type of connection	pluggable screw terminals, 8-pin		
Signal	HTL / push-pull		
Rated data digital output	24 V DC / 30 mA		
Incremental interface / RS422 (OUT) X4			
Type of connection	pluggable screw terminals, 7-polig		
Signal	RS422 / TTL		
Frequency	max. 500 kHz		
Signal delay	SinCos <-> RS422: 600 ns HTL <-> RS422: 600 ns		
Source	SinCos (X6), HTL (X10)		
Analog interface (OUT) X4			
Type of connection	pluggable screw terminals, 7-pin		
Signal	analog		
Resolution	14 bit		
Accuracy	±0.1 %		
Output	1 ms		
Frequency	4 ... 20 mA		
Load	max. 270 Ω		
SinCos interface (OUT) X5			
Type of connection	Sub-D, Buchse, 9-polig		
Signal	SinCos		
Signal level	1 V _{ss} (±20 %)		
Signal offset	2,5 V (±0,1 V)		
Frequency	max. 500 kHz		
Signal delay	SinCos <-> SinCos: 200 ns		
Source	SinCos (X6)		
USB interface X12			
Type	USB-B female connector		
Standard	USB 1.0		


Safety modules

Safety-M compact Basic module	Speed monitoring – SMC1.1	1 axis / 1 encoder system
--	----------------------------------	----------------------------------


Terminal assignment



DIP switch S1



ON		Normal operation
OFF	1	Factory setting
	2	Self-test report
	3	Programming mode




If the analog output is not used,
terminals X4.2 and X4.3 must be
bridged.


Interface	Sub-D female connector										
Terminal X5	Signal: SinCos	A	\bar{B}	B	–	0 V	–	–	–	\bar{A}	\perp
	Pin:	1	2	3	4	5	6	7	8	9	PH

Interface	Sub-D male connector										
Terminal X6	Signal: SinCos	A	\bar{B}	B	+V	0 V	–	–	–	\bar{A}	\perp
	Pin:	1	2	3	4	5	6	7	8	9	PH

+V: Power supply encoder +V DC
 0 V: Encoder power supply ground GND (0V)
 A, \bar{A} : Cosine signal / Incremental channel A
 B, \bar{B} : Sine signal / Incremental channel B
 PH \perp : Plug connector housing (Shield)



**Sub-D female connector,
9-pin
terminal X5**



**Sub-D male connector,
9-pin
terminal X6**

Safety modules

Safety-M compact Basic module


Speed monitoring – SMC1.1

1 axis / 1 encoder system

Dimensions

Dimensions in mm [inch]

Basic module



Control and diagnostic display – 8.SMCB.000

(further information can be found in the section accessories)

