SIEMENS

Product data sheet

3TG1001-1AL2



CONTACTOR TAB CONNECTOR, 3NO+1NC FOR SNAPPING ONTO STANDARD MOUNTING RAIL AC OPERATION AC 230V 45...450HZ

General technical details:

Operating current		
• at AC-3 / at 400 V / rated value	А	8.4
• at AC-1 / at 400 V / rated value	А	16
type of voltage		AC
Supply voltage frequency / for auxiliary and control current circuit / rated value		
• minimum	Hz	45
• maximum	Hz	450
Control supply voltage		
• at 50 Hz / at AC / rated value		
• minimum	V	230
• maximum	V	230
• at 60 Hz / at AC / rated value		
• minimum	V	230
• maximum	V	230
Service power / at AC-3 / at 400 V / rated value	kW	4
Number of poles		4
Number of NC contacts / for main contacts		1
Number of NC contacts / for auxiliary contacts		0
Number of NO contacts / for main contacts		3

Number of NO contacts / for auxiliary contacts		0	
tem designation / according to DIN 40719 extendable after IEC 204-2 / according to IEC 750		К	
tem designation / according to DIN EN 61346-2	_	К	
Protection class IP		IP00	
Ambient temperature			
during operating	°C	5525	
Mechanical design:			
Design of the electrical connection			
for main current circuit		tab terminals	
 for auxiliary and control current circuit 		tab terminals	
Гуре of mounting		screw and snap-on mounting onto 35 mm standard mounting rail	
series installation		Yes	
Width	mm	36	
Height	mm	62	
Depth	mm	61	
Certificates/approvals: General Product Approval	-	Declaration of	Test Certificates
		Conformity C C EG-Konf.	Special Test Certificate
other			
Declaration of Conformity			
Further information:			
nformation- and Downloadcenter (Catalogs, Brochures,) http://www.siemens.com/industrial-controls/catalogs			
ndustry Mall (Online ordering system) http://www.siemens.com/industrial-controls/mall			
CAx-Online-Generator http://www.siemens.com/cax			
IIIp.//www.siemens.com/cax			

last change:

Apr 14, 2012