1SDA054396R1

General Information

 Product ID:
 1SDA054396R1

 EAN:
 8015644554941

Catalog Description: T5N 630 PR221DS-LS/I In=630 3P F F

Long Description: Automatic moulded case circuit-breaker, SACE Tmax T5, Icu 415 V AC = 36kA, Size Iu =

630A, Electronic trip unit with against overload and as an alternative protection function against delay short circuit or protection against instantaneous short circuit, In = 630A, 3

poles, Version = Fixed, connection terminal = Front terminal

Categories

Products » Low Voltage Products and Systems » Circuit Breakers » Moulded Case Circuit Breakers » Tmax T Class

Ordering

 EAN:
 8015644554941

 Minimum Order Quantity:
 1 piece

 Customs Tariff Number:
 85362090

Dimensions

Product Net Width:140 mmProduct Net Height:205 mmProduct Net Depth:103.5 mmProduct Net Weight:5.1 kg

Container Information

Package Level 1 Units: 1 piece
Package Level 1 Width: 248 mm
Package Level 1 Height: 240 mm
Package Level 1 Length: 285 mm
Package Level 1 Gross Weight: 5.1 kg
Package Level 1 EAN: 8015644554941

Environmental

RoHS Status: Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007-01-01

Additional Information

Electrical Durability: 5000

IIT Publishing Status: Level 0 - Information enabled

Number of Poles: 3

Power Loss: Per Pole 41 W **Product Main Type:** SACE Tmax **Product Name:** T5 Rated Current (In): 630 A Rated Operational Voltage (Ue): 690 V AC Release Type: PR221DS-LS/I Standards: IEC 60947 Suitable For: T5

Suitable for Product Class: Moulded Case Circuit Breakers
Terminal Connection Type: Fixed Circuit-Breakers

Test Voltage at Industrial Frequency 3500 V

for 1 Minute:

Version: Fixed

Certificates and Declarations (Document Number)

Declaration of Conformity - CE: 1SDL000158R0033

Classifications

E-nummer:	E3180374
Object Classification Code:	Q
UNSPSC:	39121100