

# Plexo™ mechanisms IP 55

## controls and socket outlets



0 695 34



0 695 47



0 695 71



Green'Up Access socket outlets for electric vehicles

p. 598

Mechanisms supplied with cover plate  
Installation with surface-mounting boxes or flush-mounting support frames (p. 597)

Pack	Cat.Nos	Light sensitive switches, 230 V~
5	0 695 17	<b>Light sensitive switch 1 function</b> Can be used to switch a lighting circuit "ON" and "OFF" based on light conditions (nightfall, daybreak) Supplied in one piece, including photoelectric cell Maximum load: - 1400 W incandescent and halogen lamps 230 V~ - 400 VA fluorescent tubes Luminosity threshold: 0,5 to 1500 lux IP 55 - IK 07 ● Grey
5	0 695 18	<b>Photoelectric cell</b> For use with modular light sensitive switches IP 55 ● Grey

Pack	Cat.Nos	Key-operated switches 3 A - 250 V~
1	0 695 34	Supplied with RONIS key n° 455 Key removable in all position 2 N/O contacts <b>2 positions marked "0 - I"</b> ● Grey
1	0 695 35	<b>3 positions marked "I - 0 - II"</b> ● Grey

Pack	Cat.Nos	Emergency stop functions 3 A - 250 V~
1	0 695 47	Supplied with "emergency stop" label in 8 languages. Yellow cover plate, red button <b>Emergency stop button - 1 N/C contact</b> ● Grey/yellow
1	0 695 48	<b>Emergency stop with key for reset - N/O + N/C contact</b> Key RONIS n° 455 supplied Key removable in 0 position ● Grey/yellow
1	0 695 49	<b>Emergency stop - stay put 1/4 release - N/O + N/C contact</b> Key removable in 0 position ● Grey/yellow

Pack	Cat.Nos	Illuminated time lag switch - 250 V~
5	0 696 04	Electronic time lag switch - IP 55 2-wire connection Supplied with lamp Temporization: 25 s to 15 min. Maximum loads: - 1000 W incandescent and halogen 230 V~ - 400 W halogen 130 V - 400 VA ELV halogen lamps - 400 VA fluorescent lamps - 2300 W resistive (heating) ○ White ● Grey
5	0 695 04	
10	0 696 39	<b>German standard socket outlets 16 A - 250 V~</b> With earth lateral contact <b>2P+E screw terminals</b> ○ White ● Grey ○ White antimicrobial <b>2P+E automatic terminals</b> ○ White ● Grey
10	0 695 71	
5	0 707 22	

Pack	Cat.Nos	British standard socket outlets 13 A - 250 V~
10	0 695 85	<b>2P+E screw terminals</b> ● Grey

Pack	Cat.Nos	French standard socket outlets 16 A - 250 V~
10	0 696 21	<b>2P+E automatic terminals</b> With shutters for child protection ○ White ● Grey ○ White antimicrobial <b>2P+E tamperproof-screw terminals</b> ● Grey
10	0 695 51	
5	0 707 21	
5	0 695 53	<b>2P+E with flap-automatic terminals</b> Automatic opening of the flap ● Grey
5	0 695 55	

Pack	Cat.Nos	Tamperproof insert for Cat.No 0 695 53
10	0 502 99	Tamperproof insert for socket Fits directly into the plug