

Plexo

IP 55 modular mechanisms (continued)



IP 55 - IK 07
 Grey RAL 7035 / 7016
 Polycarbonate/polypropylene housing
 Temp. rating : -20 to +40 °C (+50 °C for short periods)
 Supplied with 1 flat + 1 stepped gland
 Captive terminal screws supplied in backed-off position
 Installation with surface mounting boxes or flush mounting frames

Pack	Cat. Nos.	Pilot light	
10	0695 83		Accepts E10 lamps - 5 W max. Supplied with lamp Cat. No. 0898 40 Supplied without diffusers (see below)
		Diffusers for pilot light	
10	0695 88		Colourless
10	0695 89		Green
10	0695 90		Orange
10	0695 91		Red

Pack	Cat. Nos.	Light sensitive switches - 230 V~	
		Light sensitive switch 1 function IP 55 - IP 07	
5	0695 17		Can be used to switch a lighting circuit "ON" and "OFF" based on light conditions (nightfall, daybreak) Supplied in one piece, including photo electric cell Maximum load : - 1 400 W incandescent and halogen lamps 230 V~ - 400 VA fluorescent tubes Luminosity threshold : 0.5 to 1 500 lux
		Photo-electric cell IP 55	
5	0695 18		For use with modular Microlux D light sensitive switch Cat. No. 4126 26 (see below)
		Microlux D light sensitive switch	
		Can be used to switch a lighting circuit "ON" and "OFF" based on light conditions (nightfall, daybreak) Supplied with IP 65 weatherproof photoelectric cell Power supply : 230 V~ - 50/60 Hz	
		Standard	
1	4126 26		56 programmes possible : daily, weekly or yearly programmes Output 16 A - 250 V~ - $\mu \cos \varphi = 1$ 2 000 W incandescent 2 000 VA series compensated fluorescent 1 000 W energy-saving bulb Integrated hour counter High precision clock : ± 0.1 sec per day at 25°C Working reserve : 5 years Adjustable from 3 to 100 000 lux Automatic changeover between summer/winter time Number of modules : 2 Programmed using programme transfer key Cat. No. 4128 72 Supplied with IP 65 photoelectric cell Cat. No. 4128 58

Pack	Cat. Nos.	Socket outlet 13 A - 250 V~	
10	0695 85		Panel mounting 1 gang - 13 A socket 2P + E screw terminals

Pack	Cat. Nos.	Back boxes and support frames	
		Surface mounting boxes with membrane glands	
		Equipped with removable membrane glands Direct entry of cables (No need to be cut)	
10	0696 51		1 gang - 1 entry
5	0696 72		2 gang - 1 entry
		Surface mounting boxes with membrane glands	
		Equipped with removable membrane glands Direct entry of cables (No need to be cut)	
5	0696 56		1 gang - 1 entry
5	0696 78		2 gang, horizontal mounting - 2 entries (2 top)
		Flush mounting support frame	
10	0696 81		1 gang For Plexo modular mechanisms

Pack	Cat. Nos.	Accessories	
		Modular back box IP 55 - IK 05	
		To receive Arteor modules (max. 2 modules)	
10	0695 80		Adaptor with smoked polycarbonate flap
		Lamps	
10	0694 98		230 V - 1 mA orange (indicator)
10	0694 97		230 V - 0.5 mA green (locator)
		E10 for pilot light	
10	0898 40		230 V - 5 W

For Microlux D light sensitive switch programme transfer key and software, contact us on **+44 (0) 345 605 4333**



ceiling accessories

safety lampholders and pendant sets



Pack	Cat. Nos.	Energy-saving pendant set
1	White 6603 07	<p>Conforms to EN 61000-3-2, EN 50082-1, EN 55015, EN 60929, EN 61547, EN 60928 and BS 67</p> <p>Supply voltage 230 - 240 V Mains frequency 50 Hz To be used with 13/18 W 4 pin plug-in lamps only Lamp fitting type GX24q-1 Dimming is not possible Ceiling rose has angled terminal block with clear polycarbonate shroud 8 in-line terminals with captive screws and earth terminal</p> <p>3 inch drop – energy-saving 13/18 W pendant set Lamp not supplied</p>

Pack	Cat. Nos.	Safety lampholders
20	White 0600 81	<p>T2 rated to BS 7895</p> <p>Heat resistant glass fibre reinforced PET¹ one-piece lampholder body</p> <p>Safety lampholders feature automatic isolation of brass plungers following lamp removal Plungers cannot be made live again unless lamp is in place</p> <p>B22 lampholder – short skirt</p>

Pack	Cat. Nos.	Safety lampholder + tails
20	White 8204 90	<p>T2 rated to BS 7895</p> <p>Safety lampholder + 6 inch tails</p>

Pack	Cat. Nos.	Safety batten lampholders
10	White 0600 85	<p>T2 rated to BS 7895</p> <p>Incorporate previous safety lampholders, plus : Angled terminal block with clear polycarbonate shroud Heat resistant tails to IEC 60227</p> <p>B22 lampholder – straight/short skirt 8 in-line terminals with captive screws plus earth</p>
10	0600 86	<p>B22 lampholder – straight/H.O. skirt 8 in-line terminals with captive screws plus earth</p>

Pack	Cat. Nos.	Safety pendant sets
10	White 0600 89	<p>T2 rated to BS 7895</p> <p>Combination of ceiling rose and previous safety lampholder with length of two core 0.75 mm² PVC circular flexible cable, plus : Angled terminal block with clear polycarbonate shroud 8 in-line terminals with captive screws and Heat resistant tails to IEC 60227</p> <p>6 inch drop – short skirt lampholder</p>
10	0600 90	<p>6 inch drop – H.O. skirt lampholder</p>

1 : PET – Polyethylene Terephthalate

Download the full file at

<http://assets.kempstoncontrols.com/doc/Wiring%20Accessories%20Product%20Guide.pdf>



KEMPSTON
CONTROLS