

# Isolating switches DX<sup>3</sup> - IS

from 16 A to 125 A



4 065 27

4 065 44

4 064 06

4 064 59

4 064 81



Dimensions **see e-catalogue**  
 Technical characteristics **p. 55**

AC 22 A according to IEC 60947 - 3  
 Double break contacts

Pack	Cat.Nos	Remote trip head isolating switches	
		Red handle (main device) Visible contact indication Remote tripping with associated control auxiliary (p. 66) Visual indication of the actual status of the contacts: - Closed position or fault (red indicator - I) - Open position (green indicator) on handle In case of fault when opening, the red position indicator indicates the faulty pole and the handle is in the central position	
		<b>2P - 400 V<sup>~</sup></b>	
		Nominal rating I <sub>n</sub> (A)	Number of modules
2	4 065 27	40	2
2	4 065 28	63	2
		<b>3P - 400 V<sup>~</sup></b>	
1	4 065 35	40	3
1	4 065 36	63	3
1	4 065 38	100	4.5
1	4 065 39	125	4.5
		<b>4P - 400 V<sup>~</sup></b>	
1	4 065 43	40	4
1	4 065 44	63	4
1	4 065 46	100	6
1	4 065 47	125	6

Pack	Cat.Nos	Isolating switches	
		Can be equipped with 1 DX <sup>3</sup> signalling auxiliary Cat.Nos 4 062 58 or 4 062 66	
		<b>1P - 250 V<sup>~</sup></b>	
		Nominal rating I <sub>n</sub> (A)	Number of modules
10	4 064 00	16	1
10	4 064 01	20	1
10	4 064 03	32	1
10	4 064 11	40	1
10	4 064 12	63	1
10	4 064 23	100	1
		<b>1P with indicator - 250 V<sup>~</sup></b>	
		Supplied with lamp	
10	4 064 04	20	1
10	4 064 06	32	1
		<b>2P - 400 V<sup>~</sup></b>	
10	4 064 31	16	1
10	4 064 32	20	1
10	4 064 34	32	1
5	4 064 40	40	2
5	4 064 41	63	2
5	4 064 49	100	2
5	4 064 50	125	2
		<b>2P with indicator - 400 V<sup>~</sup></b>	
		Supplied with lamp	
		Do not accept auxiliaries	
10	4 064 36	20	1
10	4 064 38	32	1
10	4 064 39	40	1
		<b>3P - 400 V<sup>~</sup></b>	
5	4 064 57	20	2
5	4 064 59	32	2
3	4 064 60	40	3
3	4 064 61	63	3
3	4 064 69	100	3
3	4 064 70	125	3
		<b>4P - 400 V<sup>~</sup></b>	
5	4 064 77	20	2
5	4 064 79	32	2
2	4 064 80	40	4
2	4 064 81	63	4
2	4 064 89	100	4
2	4 064 90	125	4



For detailed dimensions,  
**see e-catalogue**