



Main

Range of product	Clario Acti 9 Prodis Librio
Product or component type	Double OC or fault contact
Device short name	OF and OF or OF and SD
Signal contacts composition	2 C/O
[In] rated current	1 A: 130 V DC 2 A: 48 V DC 6 A: 24 V DC 3 A: 415 V AC - 50/60 Hz 6 A: 240 V AC - 50/60 Hz
9 mm pitches	1

Complementary

Range compatibility	Acti 9 DPN Vigi Acti 9 RCCB-ID Acti 9 iDPN Vigi Acti 9 C60H-DC Acti 9 C60PV-DC Acti 9 C40 Acti 9 ID C40 Acti 9 C120 Acti 9 DT40 Acti 9 DT60 Acti 9 IDc Acti 9 C120NA-DC Acti 9 iDPN Acti 9 ITG40 Acti 9 SW60-DC Acti 9 C60NA-DC Acti 9 C40 Vigi Acti 9 DT40 Vigi
Mounting mode	Fixed
Mounting support	DIN rail

Height	90 mm
Width	9 mm
Depth	73.5 mm
Net weight	38 g
Colour	White
Connections - terminals	Clamp terminal (bottom) 2 cable(s) 1.5 mm ² - flexible Clamp terminal (bottom) 1 cable(s) 0.5...2.5 mm ² - rigid Clamp terminal (bottom) 2 cable(s) 1.5 mm ² - flexible with ferrule
Wire stripping length	9 mm
Tightening torque	1 N.m

Environment

Standards	EN/IEC 60947-5-1
Product certifications	ASTA ASEFA LCIE KEMA
IP degree of protection	IP20 conforming to EN/IEC 60947-5-1
Pollution degree	3 conforming to EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	Download RoHS China Declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------