



Fuse-link, low voltage, 20 A, AC 440 V, Joint service size 1, 12 x 35 mm, BS



**Part no.** 20A 440V SIZE 1 JOINT SERVICE  
**Catalog No.** 011-9483

Similar to illustration

### Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	20
Rated voltage			AC 440 V
Construction size			Joint service size 1
Size			12 x 35 mm
Breaking Capacity		kA	33
usable for size/applications			NATO
Standard/Approval			BS
Shape			cylindrical
Standards/Regulations			BS88 DEF STAN 59-96

### Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	20
Rated voltage		V	440
Voltage type			AC
Rated switching capacity		kA	33
Utilization category			Other
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No

### Additional product information (links)

Product datasheet (pdf)	<a href="http://www1.cooperbusmann.com/pdf/76af0d86-579c-4ccc-afb5-33295785a098.pdf">http://www1.cooperbusmann.com/pdf/76af0d86-579c-4ccc-afb5-33295785a098.pdf</a>
-------------------------	---