

Connecting line



Picture can differ from actual product

Order Code : BCC06JE

BCC A324-A314-30-304-PX04A5-006

Keyfeatures

Connection	7/8" / 7/8", 0,6m, PUR
Operating voltage	300 V AC/DC
Number of conductors	4
Cable length	0,6 m
Connector type	7/8" / 7/8"
System	molded / molded

General attributes

Power-on indicator	No / No
Degree of protection as per IEC 60529	IP68 / IP68
Additional text	Enclosure type accord. to IEC 60529, when threaded together with the appropriate counterpart. Halogene Free per DIN-VDE 0472 part 815 Flame resistant per IEC 60332-1-2 Cable structure according to UL-AWM Style 20234
Function indicator (PIN 2)	No / No
Function indicator (PIN 4)	No / No
Special properties	Drag chain compatible

Electrical attributes

Switching output	No
-------------------------	----

Switching function Complementary (NO/NC)

Rated current (40 °C) 9.0 A

Operating voltage 300 V AC/DC

Mechanical attributes

Number of conductors	4
Cable length	0,6 m
Connector type	7/8" / 7/8"
Conductor cross-section	1.5 mm ²
Cable jacket material	PUR
Acceleration max. (drag chain)	20 m/s ²
Bending radius fixed cable	min. 7.5 x D
Bending radius repeated	min. 10 x D
Contact material	CuZn / CuZn
Contact carrier material	PUR / PUR
Cover nut material	GD-Zn / GD-Zn
Grip material	PUR / PUR
Ambient temp. min. (drag chain)	-20 °C
Ambient temp. max. (drag chain)	60 °C
Permiss. horizon. traverse dist.	2 m
Traverse speed max (drag chain)	200 m/min
Permiss. vert. traverse dist.	5 m
Tightening torque pigtail	1.5 Nm / 1.5 Nm
Bending cycles (in million)	> 2 Mio.
Cable diameter D	8.0 +/- 0.20 mm
Ambient temp. min. (fixed)	-20 °C
Ambient temp. max. (fixed)	80 °C
Ambient temp. min. (moving)	-20 °C

Ambient temp. max. (moving)	60 °C
System	molded / molded
Number of sockets or pins	4 / 4
Connector style (Head I)	Plug 7/8"
Connector type (Head II)	Connector 7/8"
Cable jacket colour	black