

Synergy® modern

socket outlets and shaver sockets



7310 60



7312 71



7310 89































7312 59



Flush mounting back boxes

p. 187

Front plates : clip on die cast plate with high quality satin finish; anthracite interiors; matching decorative rockers (except where indicated)
Terminal screws captive and backed off ready for cabling

Pack	Cat. Nos.	Double pole socket outlets 13 A - 250 V~	Pack	Cat. Nos.	Unswitched socket outlets 13 A - 250 V~
		Conform to BS 1363 - Part 2 : 1995 2 earth terminals Flush mounting back box : min. 25 mm deep Nominal plate dimensions : 1 gang - 89 x 89 mm 2 gang - 89 x 149 mm			Conform to BS 1363 - Part 2 : 1995 2 earth terminals Flush mounting back box : min. 25 mm deep Nominal plate dimensions : 1 gang - 89 x 89 mm 2 gang - 89 x 149 mm
		 Silver			 Silver
		 Nickel			 Nickel
1	7310 60 7312 60	 1 gang – switched	1	7310 65 7312 65	 1 gang – unswitched
1	7310 61 7312 61	 1 gang – switched + red LED power indicator	1	7310 75 7312 75	 2 gang – unswitched
1	7310 70 7312 70	 2 gang – switched			
1	7310 71 7312 71	 2 gang – switched + red LED power indicator			
		RCD sockets 13 A - 250 V~ Conform to BS 7288 : 1990 and BS 1363 - Part 2 : 1995 Stainless steel plate with fixing screws Conventional earth pin release shutter Maximum operating current 16 A Incorporate a “test and reset” button Flush mounting back box : min. 25 mm deep Nominal plate dimensions : 86 x 146 mm			Socket outlets 15 A - 250 V~ Conform to BS 546 : 1950 Flush mounting back box : min. 35 mm deep Nominal plate dimensions : 89 x 89 mm
		 Silver			 Silver
		 Nickel			 Nickel
1	7310 97 7312 97	 RCD unit 2 gang DP 30 mA active	1	7310 88 7312 88	 1 gang – unswitched
		Active (electronically latched) - trips in the event of a power failure - suitable in applications where automatic restoration of supply would be hazardous, e.g. machinery, power tools	1	7310 89 7312 89	 1 gang – switched
		Passive (mechanically latched) - does not trip in the event of a power failure - suitable in applications where automatic restoration of supply is required, e.g. fridge, freezer, unmanned areas			
1	7310 98 7312 98	 RCD unit 2 gang DP 30 mA passive			
					Socket outlets 2 A - 250 V~ Conform to BS 546 : 1950 Flush mounting back box : min. 25 mm deep Nominal plate dimensions : 89 x 89 mm
					 Silver
					 Nickel
1	7310 59 7312 59		1	7310 59 7312 59	 1 gang – unswitched
					Socket outlets 5 A - 250 V~ Conform to BS 546 : 1950 Flush mounting back box : min. 25 mm deep Nominal plate dimensions : 89 x 89 mm
					 Silver
					 Nickel
1	7310 68 7312 68		1	7310 68 7312 68	 1 gang – unswitched
			1	7310 69 7312 69	 1 gang – switched
					Shaver sockets Conform to BS EN 61558-2-5 : 1998 IP 24 For use with European, British, American and Australian 2 pin plugs Screwless live and neutral terminals Double wound isolating transformer Automatic self-resetting overload feature Plug insertion operates microswitch which energises transformer Flush mounting back box : min. 47 mm deep Nominal plate dimensions : 149 x 89 mm
					 Silver
					 Nickel
1	7310 90 7312 90		1	7310 90 7312 90	 Supply : 230 V - 50/60 Hz Output : 230/120 V - 20 VA max.

Synergy® modern

fused connection units



7310 35



7312 34



7310 30



7312 32



Flush mounting back boxes

p. 187



7310 37




7312 36



7310 31















7312 33



Red LED power indicator

Front plates : clip on die cast plate with high quality satin finish; anthracite interiors; matching decorative rockers (except where indicated)
Terminal screws captive and backed off ready for cabling

Pack	Cat. Nos.		Fused connection units 13 A - 250 V~	
			Conform to BS 1363 - Part 4 : 1995 Fuse drawer retained by quarter turn catch, drawer padlockable in open position for safety Flush mounting back box : min. 25 mm deep Nominal plate dimensions : 89 x 89 mm	
	Silver	Nickel	Switched	
1	7310 34	7312 34		Switched, DP
1	7310 35	7312 35		Switched, DP + red LED power indicator
1	7310 36	7312 36		Switched, DP with cord outlet
1	7310 37	7312 37		Switched, DP with cord outlet + red LED power indicator

Pack	Cat. Nos.		Fused connection units 13 A - 250 V~ (continued)	
			Conform to BS 1363 - Part 4 : 1995 Fuse drawer retained by quarter turn catch, drawer padlockable in open position for safety Flush mounting back box : min. 25 mm deep Nominal plate dimensions : 89 x 89 mm	
	Silver	Nickel	Unswitched	
1	7310 30	7312 30		Unswitched
1	7310 31	7312 31		Unswitched + red LED power indicator
1	7310 32	7312 32		Unswitched with cord outlet
1	7310 33	7312 33		Unswitched with cord outlet + red LED power indicator

Download the full file at

<http://assets.kempstoncontrols.com/doc/Legrand%20Wiring%20Devices%202012.pdf>



KEMPSTON
CONTROLS