



M8 - M12 STANDARD SENSORS

- 1.5 – 4mm sensing distance
- Cable and connector types
- LED indication
- PNP and NPN types available
- N/O and N/C types available



GENERAL SPECIFICATIONS

Sn mm	Size	Mounting Flush/ Non Flush	Connection	Supply	Frequency (Max)	Max Load	LED Ind	Type	Output	Part Number	
1.5	M8X1 "Standard Cable Type" 	Flush	3 Wire 2m	10-35V DC	2KHz	200mA	1 LED	PNP	N/O	ICCA 0814	
									N/C	ICCA 0815	
									NPN	N/O	ICCA 0812
										N/C	ICCA 0813
2	M8X1 "Standard Cable Type" 	Non Flush	3 Wire 2m	10-35V DC	2KHz	200mA	1 LED	PNP	N/O	INCA 0814	
									N/C	INCA 0815	
									NPN	N/O	INCA 0812
										N/C	INCA 0813
1.5	M8X1 "Standard Connector Type" 	Flush	Plug in M 8 3 Pin	10-35V DC	2KHz	200mA	1 LED	PNP	N/O	ICLD 0814	
									N/C	ICLD 0815	
									NPN	N/O	ICLD 0812
										N/C	ICLD 0813
2	M8X1 "Standard Connector Type" 	Non Flush	Plug in M8 3 Pin	10-35V	2KHz	200mA	1 LED	PNP	N/O	INLD 0814	
									N/C	INLD 0815	
									NPN	N/O	INLD 0812
										N/C	INLD 0813
2	M12X1 "Standard Cable Type" 	Flush	3 Wire 2m	10-35V DC	2KHz	200mA	1 LED	PNP	N/O	ILCT 1214	
									N/C	ILCT 1215	
									NPN	N/O	ILCT 1212
										N/C	ILCT 1213
4	M12X1 "Standard Cable Type" 	Non Flush	3 Wire 2m	10-35V DC	1KHz	200mA	1 LED	PNP	N/O	IPCT 1214	
									N/C	IPCT 1215	
									NPN	N/O	IPCT 1212
										N/C	IPCT 1213
2	M12X1 "Standard Connector Type" 	Flush	Plug in M12 4 Pin	10-35V	2KHz	200mA	1 LED	PNP	N/O	ILLI 1214	
									N/C	ILLI 1215	
									NPN	N/O	ILLI 1212
										N/C	ILLI 1213
4	M12X1 "Standard Connector Type" 	Non Flush	Plug in M12 4 Pin	10-35V DC	1KHz	200mA	1 LED	PNP	N/O	IPLI 1214	
									N/C	IPLI 1215	
									NPN	N/O	IPLI 1212
										N/C	IPLI 1213