

Identification	Han® Axial Screw Module	Han® Axial Screw Module	Han® Axial Screw Module	Han® Axial Screw Module
Number of contacts	1	2	2	3
Termination	Axial screw terminal	Axial screw terminal	Axial screw terminal	Axial screw terminal
Electrical data acc. to DIN EN 61 984				
Current / voltage	200 A / 1000 V	100 A / 1000 V	40 A / 1000 V	40 A / 690 V
Wire gauge	40 - 70 mm <sup>2</sup>	16 - 35 mm <sup>2</sup>	2.5 - 8 mm <sup>2</sup>	6 - 10 mm <sup>2</sup>
Male insert (M)	09 14 001 2662	09 14 002 2651	09 14 002 2601	09 14 003 2602
Female insert (F)	09 14 001 2762	09 14 002 2751	09 14 002 2701	09 14 003 2702

Identification	Han® C Module	Han® CC Protected Mod.	Han E® Module	Han® EE Module
Number of contacts	3	4	6	8
Termination	Crimp terminal	Crimp terminal	Crimp terminal	Crimp terminal
Electrical data acc. to DIN EN 61 984				
Current / voltage	40 A / 400/690 V	40 A / 830 V	16 A / 500 V	16 A / 400 V
Wire gauge	1.5 - 6 mm <sup>2</sup>	1.5 - 6 mm <sup>2</sup>	0.5 - 4 mm <sup>2</sup>	0.5 - 4 mm <sup>2</sup>
Male insert (M)	09 14 003 3001	09 14 004 3041	09 14 006 3001	09 14 008 3001
Female insert (F)	09 14 003 3101	09 14 004 3141	09 14 006 3101	09 14 008 3101

Identification	Han E® Protected Mod.	Han® EEE Module	Han® HV Module	Han® ES Module
Number of contacts	6	20	2	5
Termination	Axial screw terminal	Axial screw terminal	Axial screw terminal	Cage clamp terminal
Electrical data acc. to DIN EN 61 984				
Current / voltage	16 A / 830 V	16 A / 500 V	16 A / 2900/5000 V	16 A / 400 V
Wire gauge	0.5 - 4 mm <sup>2</sup>	0.5 - 4 mm <sup>2</sup>	0.5 - 4 mm <sup>2</sup>	0.14 - 2.5 mm <sup>2</sup>
Male insert (M)	09 14 006 3041	09 14 020 3001	09 14 002 3021	09 14 005 2616
Female insert (F)	09 14 006 3141	09 14 020 3101	09 14 002 3121	09 14 005 2716