



KEMPSTON CONTROLS

Honeywell

Operating Force (OF)	0,19 N m [1.7 in lb] max.
Full Overtravel Force	8,13 N m [6 in lb] max.
Release Force	0,04 N m [0.35 in lb] min.
Pretravel (PT)	20° max.
Overtravel (OT)	30° min.
Differential Travel (DT)	12° max.
Product Type	MICRO SWITCH™ Compact Limit Switches
Actuator	Side Rotary
Lever Type	Rod - Adjustable
Circuitry	1NC 1NO SPDT Snap Action, Double Break
Ampere Rating	10 A Ind./0.8 A Res./0.4 Res./0.1 A Res.
Supply Voltage	120 Vac, 240 Vac, 480 Vac/115 Vdc/230 Vdc/550 Vdc
Housing Material	Zinc Die-Cast
Termination Type	20 mm [0.79 in] Conduit
Housing Type	Compact / Non Plug-In
Series Name	LS
Sealing	NEMA 1, 3, 4, 6, 13
Operating Temperature	-29 °C to 71 °C [-20 °F to 160 °F]
Comment	Solder terminals, 5 in (127mm) aluminum rod actuator
UNSPSC Code	302119
UNSPSC Commodity	302119 Switches and controls and relays
Sealed	Industrial