

Synergy® Authentic

British standard socket outlets



8330 65



8332 75



8330 60



8334 61



8332 71

Slim front plate:

BSS: Plates made of austenitic Stainless Steel - non-magnetic - grade 304 L

PSS: Plates made of Stainless Steel + rust resistance

G: Plates made of Stainless Steel + rust resistance

Terminal screws captive and backed off ready for cabling - large angled terminal entries

Compact mechanism for maximum wiring space

Pack	Cat.Nos.	Socket outlets 13 A - 250 V~
		Conform to BS 1363 : Part. 2 With safety shutter mechanism Flush mounting back box : min. 25 mm deep ASTA licence
		1 gang unswitched Nominal plate dimensions : 86 x 86 mm
1	8330 65	● Brushed stainless steel
1	8332 65	● Polished stainless steel
1	8334 65	● Gold
		2 gang unswitched Nominal plate dimensions : 86 x 146 mm
1	8330 75	● Brushed stainless steel
1	8332 75	● Polished stainless steel
1	8334 75	● Gold

Pack	Cat.Nos.	Double pole socket outlets 13 A - 250 V~
		Conform to BS 1363 : Part. 2 With safety shutter mechanism Flush mounting back box : min. 25 mm deep ASTA licence
		1 gang switched Nominal plate dimensions : 86 x 86 mm
1	8330 60	● Brushed stainless steel
1	8332 60	● Polished stainless steel
1	8334 60	● Gold
		1 gang switched with blue LED power indicator Nominal plate dimensions : 86 x 86 mm
1	8330 61	● Brushed stainless steel
1	8332 61	● Polished stainless steel
1	8334 61	● Gold
		2 gang switched Nominal plate dimensions : 86 x 146 mm
1	8330 70	● Brushed stainless steel
1	8332 70	● Polished stainless steel
1	8334 70	● Gold
		2 gang switched with blue LED power indicator Nominal plate dimensions : 86 x 146 mm
1	8330 71	● Brushed stainless steel
1	8332 71	● Polished stainless steel
1	8334 71	● Gold
		2 gang switched outboard for standard and clean earth applications Nominal plate dimensions : 86 x 146 mm
1	8330 74	● Brushed stainless steel
1	8332 74	● Polished stainless steel
1	8334 74	● Gold

Pack	Cat.Nos.	Key switched socket outlets 13 A - 250 V~
		Conform to BS 1363 - Part. 2 : 1995 Flush mounting back box : min. 35 mm deep Nominal plate dimensions : 86 x 146 mm
1	8216 57	● Brushed stainless steel
1	8216 58	● Polished stainless steel
1	8216 59	● Gold



8332 97



8334 89



8330 69



8332 59



8330 44

Slim front plate:

BSS: Plates made of austenitic Stainless Steel - non-magnetic - grade 304 L

PSS: Plates made of Stainless Steel + rust resistance

G: Plates made of Stainless Steel + rust resistance

Terminal screws captive and backed off ready for cabling - large angled terminal entries

Compact mechanism for maximum wiring space

Pack	Cat.Nos.	RCD sockets 13 A - 250 V \sim
		Conform to BS 7288 : 1990 and BS 1363 - Part 2 : 1995 Conventional earth pin release shutter Maximum operating current 16 A Electronic RCD module with a membrane switch for "test and reset" Flush mounting back box : min. 25 mm deep
		ELO - DP 30 mA - active Trips in the event of a power failure Ideal for applications where it is desirable to prevent automatic reactivation of equipment after a power failure. For hazardous, e.g. machinery, power tools
1	8330 85	1 gang - Nominal plate dimensions : 86 x 86 mm
1	8332 85	● Brushed stainless steel
1	8334 85	● Polished stainless steel
		● Gold
1	8330 97	2 gang - Nominal plate dimensions : 86 x 146 mm
1	8332 97	● Brushed stainless steel
1	8334 97	● Polished stainless steel
		● Gold
		ELR - DP 30 mA - passive Trips in the event of a power failure Ideal for applications where it is desirable to automatically reactivate equipment after a power failure. E.g. fridge, freezer, unmanned areas
1	8330 86	1 gang - Nominal plate dimensions : 86 x 86 mm
1	8332 86	● Brushed stainless steel
1	8334 86	● Polished stainless steel
		● Gold
1	8330 98	2 gang - Nominal plate dimensions : 86 x 146 mm
1	8332 98	● Brushed stainless steel
1	8334 98	● Polished stainless steel
		● Gold

Pack	Cat.Nos.	Socket outlets 15 A - 250 V \sim
		Conform to BS 546 Patented 3 pin safety shutter mechanism, Flush mounting back box : min. 35 mm deep Nominal plate dimensions : 86 x 86 mm
		1 gang unswitched
1	8330 88	● Brushed stainless steel
1	8332 88	● Polished stainless steel
1	8334 88	● Gold
		1 gang switched - single pole
1	8330 89	● Brushed stainless steel
1	8332 89	● Polished stainless steel
1	8334 89	● Gold

Pack	Cat.Nos.	Socket outlets 5 A - 250 V \sim
		Conform to BS 546 Patented 3 pin safety shutter mechanism, Flush mounting back box : min. 25 mm deep
		1 gang unswitched Nominal plate dimensions : 86 x 86 mm
1	8330 68	● Brushed stainless steel
1	8332 68	● Polished stainless steel
1	8334 68	● Gold
		1 gang switched - single pole Nominal plate dimensions : 86 x 146 mm
1	8330 69	● Brushed stainless steel
1	8332 69	● Polished stainless steel
1	8334 69	● Gold
		Socket outlets 2 A - 250 V\sim
		Conform to BS 546 Flush mounting back box : min. 25 mm deep Nominal plate dimensions : 86 x 86 mm
		1 gang unswitched
1	8330 59	● Brushed stainless steel
1	8332 59	● Polished stainless steel
1	8334 59	● Gold
		Double USB sockets
		Flush mounting back box : min. 40 mm deep Input voltage: 110 V/ 230 V Comply with IEC 62684 5 V (output) - 2400 mA Wiring with 1.5 mm ² and 2.5 mm ² (only live and neutral)
1	8330 44	● Brushed stainless steel
1	8332 44	● Polished stainless steel
1	8334 44	● Gold

Pack	Cat.Nos.	Switched USB sockets
		Socket outlets conform to BS 1363 - Part 2
		2 gang 13 A single pole switched + USB
1	8200 23	● Brushed stainless steel
1	8200 24	● Polished stainless steel
1	8200 25	● Gold

Download the full file at

<http://assets.kempstoncontrols.com/doc/Synergy%20Wiring%20Accessories.pdf>



KEMPSTON
CONTROLS