

Auxiliary Contacts

A Mechanically Held Contactor with a 2-wire control module uses 1NC auxiliary contact as standard for the control wiring circuit. The Mechanically Held Contactor with a 3-wire control module uses 1NO-1NC auxiliary contacts as standard for the control wiring circuit. See **Table 37-24** for possible additional auxiliary contact configurations.

Table 37-24. Auxiliary Contact Configurations

2-Wire	3-Wire
None 1NO (single-pole) 2NO (double-pole) 1NC (double-pole) 1NO-1NC (NO single pole, NC double-pole) 2NO-1NC (double-pole)	1NC (double-pole) 1NO (double-pole) 1NO-1NC (double-pole)



Auxiliary Contacts

Table 37-25. Auxiliary Contacts

Auxiliary Block	Catalog Number	Price U.S. \$
Single-Pole	C320AMH1	
Double-Pole	C320AMH2	

Replacement Parts

Magnet Coils for the Base Contactor



Magnetic Coils

Table 37-26. Magnetic Coils

Coil Voltage	Catalog Number	Price U.S. \$
115 – 120V 60 Hz/110V 50 Hz	9-3242-1	
230 – 240V 60 Hz/220V 50 Hz	9-3242-2	
460 – 480V 60 Hz/440V 50 Hz	9-3242-3	
575 – 600V 60 Hz/550V 50 Hz	9-3242-4	
200 – 208V 60 Hz	9-3242-5	
265 – 277V 60 Hz/240V 50 Hz	9-3242-6	
24V 60 Hz/20V 50 Hz	9-3242-7	
28V 60 Hz/24V 50 Hz	9-3242-8	
347V 60 Hz	9-3242-9	