



8332 97



8334 89



8330 69



8332 59



8330 44

Slim front plate:

BSS: Plates made of austenitic Stainless Steel - non-magnetic - grade 304 L

PSS: Plates made of Stainless Steel + rust resistance

G: Plates made of Stainless Steel + rust resistance

Terminal screws captive and backed off ready for cabling - large angled terminal entries

Compact mechanism for maximum wiring space

Pack	Cat.Nos.	RCD sockets 13 A - 250 V \sim
		Conform to BS 7288 : 1990 and BS 1363 - Part 2 : 1995 Conventional earth pin release shutter Maximum operating current 16 A Electronic RCD module with a membrane switch for "test and reset" Flush mounting back box : min. 25 mm deep
		ELO - DP 30 mA - active Trips in the event of a power failure Ideal for applications where it is desirable to prevent automatic reactivation of equipment after a power failure. For hazardous, e.g. machinery, power tools
1	8330 85	1 gang - Nominal plate dimensions : 86 x 86 mm
1	8332 85	● Brushed stainless steel
1	8334 85	● Polished stainless steel
		● Gold
1	8330 97	2 gang - Nominal plate dimensions : 86 x 146 mm
1	8332 97	● Brushed stainless steel
1	8334 97	● Polished stainless steel
		● Gold
		ELR - DP 30 mA - passive Trips in the event of a power failure Ideal for applications where it is desirable to automatically reactivate equipment after a power failure. E.g. fridge, freezer, unmanned areas
1	8330 86	1 gang - Nominal plate dimensions : 86 x 86 mm
1	8332 86	● Brushed stainless steel
1	8334 86	● Polished stainless steel
		● Gold
1	8330 98	2 gang - Nominal plate dimensions : 86 x 146 mm
1	8332 98	● Brushed stainless steel
1	8334 98	● Polished stainless steel
		● Gold

Pack	Cat.Nos.	Socket outlets 15 A - 250 V \sim
		Conform to BS 546 Patented 3 pin safety shutter mechanism, Flush mounting back box : min. 35 mm deep Nominal plate dimensions : 86 x 86 mm
		1 gang unswitched
1	8330 88	● Brushed stainless steel
1	8332 88	● Polished stainless steel
1	8334 88	● Gold
		1 gang switched - single pole
1	8330 89	● Brushed stainless steel
1	8332 89	● Polished stainless steel
1	8334 89	● Gold

Pack	Cat.Nos.	Socket outlets 5 A - 250 V \sim
		Conform to BS 546 Patented 3 pin safety shutter mechanism, Flush mounting back box : min. 25 mm deep
		1 gang unswitched Nominal plate dimensions : 86 x 86 mm
1	8330 68	● Brushed stainless steel
1	8332 68	● Polished stainless steel
1	8334 68	● Gold
		1 gang switched - single pole Nominal plate dimensions : 86 x 146 mm
1	8330 69	● Brushed stainless steel
1	8332 69	● Polished stainless steel
1	8334 69	● Gold
		Socket outlets 2 A - 250 V\sim
		Conform to BS 546 Flush mounting back box : min. 25 mm deep Nominal plate dimensions : 86 x 86 mm
		1 gang unswitched
1	8330 59	● Brushed stainless steel
1	8332 59	● Polished stainless steel
1	8334 59	● Gold
		Double USB sockets
		Flush mounting back box : min. 40 mm deep Input voltage: 110 V/ 230 V Comply with IEC 62684 5 V (output) - 2400 mA Wiring with 1.5 mm ² and 2.5 mm ² (only live and neutral)
1	8330 44	● Brushed stainless steel
1	8332 44	● Polished stainless steel
1	8334 44	● Gold

Pack	Cat.Nos.	Switched USB sockets
		Socket outlets conform to BS 1363 - Part 2
		2 gang 13 A single pole switched + USB
1	8200 23	● Brushed stainless steel
1	8200 24	● Polished stainless steel
1	8200 25	● Gold

Synergy® Authentic

fan switch and double pole switches



8334 09



8330 10



8332 16



8334 21



8334 12



8330 22



8332 23

Slim front plate:

BSS: Plates made of austenitic Stainless Steel - non-magnetic - grade 304 L

PSS: Plates made of Stainless Steel + rust resistance

G: Plates made of Stainless Steel + rust resistance

Terminal screws captive and backed off ready for cabling - large angled terminal entries

Compact mechanism for maximum wiring space

Pack	Cat.Nos.	3 pole fan switch 10 A - 250 V~
1	8330 09	Conform to BS EN 60669-1 : 2000 With integrated padlockable safety block in OFF position Flush mounting back box : min. 25 mm deep Nominal plate dimensions : 86 x 86 mm ● Brushed stainless steel ● Polished stainless steel ● Gold
1	8332 09	
1	8334 09	
Double pole switches 20 A - 250 V~ Conform to BS EN 60669-1 Flush mounting back box : min. 25 mm deep Use cord outlet accessory Cat.No 7300 53 p.38 for external cord outlet Nominal plate dimensions : 86 x 86 mm		
1	8330 10	DP switch ● Brushed stainless steel ● Polished stainless steel ● Gold
1	8332 10	
1	8334 10	
1	8330 16	DP switch + cord outlet + blue LED power indicator ● Brushed stainless steel ● Polished stainless steel ● Gold
1	8332 16	
1	8334 16	
1	8330 12	DP switch + blue LED power indicator ● Brushed stainless steel ● Polished stainless steel ● Gold
1	8332 12	
1	8334 12	

Pack	Cat.Nos.	Double pole switches 45 A - 250 V~
Conform to BS EN 60669-1 Flush mounting back box : min. 45 mm deep		
1 gang switch Nominal plate dimensions : 86 x 86 mm ● Brushed stainless steel ● Polished stainless steel ● Gold		
1	8330 22	
1	8332 22	
1	8334 22	
1 gang switch + blue LED power indicator Nominal plate dimensions : 86 x 86 mm ● Brushed stainless steel ● Polished stainless steel ● Gold		
1	8330 23	
1	8332 23	
1	8334 23	
1 gang switch + blue LED power indicator large plate Nominal plate dimensions : 146 x 86 mm ● Brushed stainless steel ● Polished stainless steel ● Gold		
1	8330 21	
1	8332 21	
1	8334 21	

Download the full file at

<http://assets.kempstoncontrols.com/doc/Synergy%20Wiring%20Accessories.pdf>



KEMPSTON
CONTROLS