

1) Output function, 2) Operating voltage, 3) Sn, light/dark, 4) Optical axis receiver, 5) Optical axis emitter



### Basic features

Approval/Conformity	CE cULus EAC WEEE
Basic standard	IEC 60947-5-2
Principle of operation	Photoelectric sensor
Series	6K
Style	Square Connection 90°

### Electrical data

No-load current $I_0$ max. at $U_e$	30 mA
Operating voltage $U_b$	10...30 VDC
Rated operating current $I_e$	100 mA
Rated operating voltage $U_e$ DC	24 V
Ripple max. (% of $U_e$ )	12 %
Switching frequency	1000 Hz
Turn-off delay $t_{off}$ max.	0.5 ms
Turn-on delay $t_{on}$ max.	0.5 ms
Voltage drop $U_d$ max. at $I_e$	2.4 V

### Display/Operation

Adjuster	button
Display	Output function- LED yellow LED green: Power
Setting	Rated switching distance (Sn) Light-on/dark-on Teach mode Stand./Dyn./Obj.

### Environmental conditions

Ambient temperature	-20...60 °C
EN 60068-2-27, Shock	Half-sinus, 30 g <sub>n</sub> , 11 ms, 3x6
EN 60068-2-6, Vibration	10...55 Hz, amplitude 0.5 mm, 3x30 min
IP rating	IP67
IP rating per DIN 40050	IP69K

### Electrical connection

Connection	Connector, M8x1-Male, 3-pin
Polarity reversal protected	yes
Short-circuit protection	yes

### Functional safety

MTTF (40 °C)	432 a
--------------	-------

### Material

Housing material	ABS
Material sensing surface	PMMA

## Mechanical data

Dimension	12 x 41.5 x 21.6 mm
Mounting part	Screw M3

## Optical features

Ambient light max.	5000 Lux
Average power Po max.	390 µW
Beam characteristic	Focused
Laser class per IEC 60825-1	1
Light spot size	Ø 1.2 mm at 120 mm
Light type	Laser red light
Principle of optical operation	Diffuse sensor, triangulation
Pulse duration t max.	3000 µs
Pulse frequency	5 kHz
Pulse power Pp max.	3.5 mW
Special optical feature	Background suppression
Switching function, optical	Light/dark switching
Wave length	650 nm

## Output/Interface

Switching output	PNP normally open/normally closed (NO/NC)
------------------	---

## Range/Distance

Distance deviation 18 % max. (% of Sr)	7 % to 90 % rem.
Range	4...120 mm
Rated operating distance Sn	120 mm Adjustable

## Remarks

The sensor is functional again after the overload has been eliminated.

When using as a UL product the ambient temperature Ta max. must not exceed 50°C.

Only for applications per NFPA 79 (machines with a supply voltage of maximum 600 V). Use an R/C (CYJV2) cable with suitable properties for attaching the device.

For additional information, refer to user's guide.

Order accessories separately.

Do not press key using a pointed tool.

Reference object (target): gray card, 200 x 200, 90 % remission, axial approach.


For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

## Connector Drawings




## Wiring Diagrams



Opto Symbols



Warning Symbols



LASER CLASS 1 per IEC 60825-1