



KEMPSTON CONTROLS

Honeywell

Availability	Global
Operating Force (OF)	2,50 N to 6,67 N [9 oz to 24 oz]
Release Force	1,11 N [0.25 lb] min.
Pretravel (PT)	1,98 mm [0.078 in] max.
Overtravel (OT)	5,56 mm [0.219 in] min.
Differential Travel (DT)	0,05 mm [0.002 in] max.
Product Type	Enclosed Switches
Actuator	Top Plunger
Circuitry	1NC 1NO SPDT Snap Action
Ampere Rating	15 A Ind./2 A Ind./0.5 A Res./0.25 A Res.
Supply Voltage	125 Vac, 250 Vac, 480 Vac/600 Vac/125 Vdc/250 Vdc
Housing Material	Zinc Die-Cast
Termination Type	0.5 in - 14NPT Conduit
Housing Type	Split Housing, Side Mount
Series Name	E6/V6
Sealing	IP66; NEMA 1, 3, 4
UL File #	E12252
Operating Temperature	-32 °C to 71 °C [-25 °F to 160 °F]
Comment	With seal boot on plunger, 1/4-32 UNEF threaded plunger
Agency Approvals and Standards	UL, CSA
UNSPSC Code	302119
UNSPSC Commodity	302119 Switches and controls and relays
Sealed	Industrial