



LL3-DC06

LL3

FIBERS

SICK
Sensor Intelligence.



Ordering information

Type	Part no.
LL3-DC06	5326017

Included in delivery: BF-WLL160-13 (1), FC (1)

Other models and accessories → www.sick.com/LL3

Detailed technical data

Features

Device type	Fibers
Detection principle	Proximity system
For fiber-optic sensor	GLL170(T), WLL180T
Fiber length	2 m
Fiber material	Polymethylmethacrylat (PMMA)
Jacket material	Polyethylen (PE)
Fiber head material	Acrylnitril-Butadien-Styrol (ABS)
Outer diameter, fiber-optic cable connection	1.3 mm
Fiber-optic cable cuttable	✓ ¹⁾
Fiber-optic head design	Flat type, 90° deflection
Fiber arrangement	Multi-fiber
Core structure	S: 9 x Ø 0,25 mm, R: 9 x Ø 0,25 mm Multi-fiber
Bend radius, fibre-optic cable	4 mm
Angle of dispersion < 60°	Yes
Compatibility with infrared light (1,450 nm)	No
Ambient operating temperature	0 °C ... +70 °C
Application	High flexible (static), Robotics (dynamic flexible), lcd / clear material / semiconductor
Highly flexible/elastic fibers (bend radius 1–4 mm)	Yes
Adapter end sleeves required	Yes
Angle of dispersion	30.22°
Integrated lens	Yes
Minimal object diameter	0.4 mm ²⁾
Included with delivery	Adapter sleeves, BF-WLL160-13 (1.3 mm) adapter sleeves, FC fiber cutter (5304141)
Compatibility tip adapters	No

¹⁾ FC fiber optic cable cutter included in delivery.

²⁾ Minimum detectable object was determined at optimum measuring distance and optimum setting.

Mechanics/electronics

Bend radius, fibre-optic cable	4 mm
Ambient operating temperature	0 °C ... +70 °C

Classifications

ECI@ss 5.0	27270905
ECI@ss 5.1.4	27270905
ECI@ss 6.0	27270905
ECI@ss 6.2	27270905
ECI@ss 7.0	27270905
ECI@ss 8.0	27270905
ECI@ss 8.1	27270905
ECI@ss 9.0	27270905
ETIM 5.0	EC002651
ETIM 6.0	EC002651
UNSPSC 16.0901	39121528

Sensing ranges with WLL180T

Operating mode 16 µs	4 mm ... 15 mm
Operating mode 70 µs	2 mm ... 22 mm
Operating mode 250 µs	0 mm ... 23 mm
Operating mode 2 ms	0 mm ... 25 mm
Operating mode 8 ms	0 mm ... 25 mm

Sensing ranges with GLL170


Operating mode 250 µs	2 mm ... 9 mm
------------------------------	---------------

Sensing ranges with GLL170T

Operating mode 50 µs	0 mm ... 11 mm
Operating mode 250 µs	0 mm ... 12 mm

Dimensional drawing (Dimensions in mm (inch))

LL3-DC06



SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

WORLDWIDE PRESENCE:

Contacts and other locations –www.sick.com