

MCBs DX³ 10000 - 16 kA

thermal magnetic circuit breakers from 1 A to 125 A

NEW



4088 69



4089 43



4091 11



4092 03

Dimensions **p. 65**
 Technical information **p. 59-60**

Conform to IEC 60898-1

Breaking capacity

10000 - IEC 60898-1 - 400 V~

16 kA - IEC 60947-2 - 400 V~

Can be equipped with DX³ auxiliaries and accessories **p. 58**

MCBs DX³ 10000 - 16 kA - B curve

| Pack | Cat. Nos. | Nominal rating I _n (A) | Number of modules |
|-------------------------------|----------------|-----------------------------------|-------------------|
| Single pole 230/400 V~ | | | |
| | B curve | | |
| 1 | 4088 65 | 1 | 1 |
| 1 | 4088 66 | 2 | 1 |
| 1 | 4088 67 | 3 | 1 |
| 1 | 4088 69 | 6 | 1 |
| 1 | 4088 70 | 10 | 1 |
| 1 | 4088 72 | 16 | 1 |
| 1 | 4088 73 | 20 | 1 |
| 1 | 4088 74 | 25 | 1 |
| 1 | 4088 75 | 32 | 1 |
| 1 | 4088 76 | 40 | 1 |
| 1 | 4088 78 | 63 | 1 |
| Double pole 230/400 V~ | | | |
| 1 | 4089 35 | 1 | 2 |
| 1 | 4089 36 | 2 | 2 |
| 1 | 4089 37 | 3 | 2 |
| 1 | 4089 39 | 6 | 2 |
| 1 | 4089 40 | 10 | 2 |
| 1 | 4089 42 | 16 | 2 |
| 1 | 4089 43 | 20 | 2 |
| 1 | 4089 44 | 25 | 2 |
| 1 | 4089 45 | 32 | 2 |
| 1 | 4089 46 | 40 | 2 |
| 1 | 4089 48 | 63 | 2 |
| Triple pole 400 V~ | | | |
| 1 | 4089 84 | 1 | 3 |
| 1 | 4089 85 | 2 | 3 |
| 1 | 4089 86 | 3 | 3 |
| 1 | 4089 88 | 6 | 3 |
| 1 | 4089 89 | 10 | 3 |
| 1 | 4089 91 | 16 | 3 |
| 1 | 4089 92 | 20 | 3 |
| 1 | 4089 93 | 25 | 3 |
| 1 | 4089 94 | 32 | 3 |
| 1 | 4089 95 | 40 | 3 |
| 1 | 4089 96 | 50 | 3 |
| 1 | 4089 97 | 63 | 3 |
| Four pole 400 V~ | | | |
| 1 | 4090 58 | 1 | 4 |
| 1 | 4090 62 | 6 | 4 |
| 1 | 4090 63 | 10 | 4 |
| 1 | 4090 65 | 16 | 4 |
| 1 | 4090 66 | 20 | 4 |
| 1 | 4090 67 | 25 | 4 |
| 1 | 4090 68 | 32 | 4 |
| 1 | 4090 69 | 40 | 4 |
| 1 | 4090 70 | 50 | 4 |
| 1 | 4090 71 | 63 | 4 |

MCBs DX³ 10000 - 16 kA - C curve

| Pack | Cat. Nos. | Nominal rating I _n (A) | Number of modules |
|-------------------------------|----------------|-----------------------------------|-------------------|
| Single pole 230/400 V~ | | | |
| | C curve | | |
| 1 | 4091 07 | 1 | 1 |
| 1 | 4091 08 | 2 | 1 |
| 1 | 4091 09 | 3 | 1 |
| 1 | 4091 11 | 6 | 1 |
| 1 | 4091 12 | 10 | 1 |
| 1 | 4091 14 | 16 | 1 |
| 1 | 4091 15 | 20 | 1 |
| 1 | 4091 16 | 25 | 1 |
| 1 | 4091 17 | 32 | 1 |
| 1 | 4091 18 | 40 | 1 |
| 1 | 4091 19 | 50 | 1 |
| 1 | 4091 20 | 63 | 1 |
| 1 | 4091 40 | 80 | 1 |
| Double pole 230/400 V~ | | | |
| 1 | 4091 95 | 1 | 2 |
| 1 | 4091 96 | 2 | 2 |
| 1 | 4091 97 | 3 | 2 |
| 1 | 4091 99 | 6 | 2 |
| 1 | 4092 00 | 10 | 2 |
| 1 | 4092 02 | 16 | 2 |
| 1 | 4092 03 | 20 | 2 |
| 1 | 4092 04 | 25 | 2 |
| 1 | 4092 05 | 32 | 2 |
| 1 | 4092 06 | 40 | 2 |
| 1 | 4092 07 | 50 | 2 |
| 1 | 4092 08 | 63 | 2 |
| 1 | 4092 28 | 80 | 3 |
| 1 | 4092 29 | 100 | 3 |
| 1 | 4092 30 | 125 | 3 |
| Triple pole 400 V~ | | | |
| 1 | 4092 47 | 1 | 3 |
| 1 | 4092 48 | 2 | 3 |
| 1 | 4092 49 | 3 | 3 |
| 1 | 4092 51 | 6 | 3 |
| 1 | 4092 52 | 10 | 3 |
| 1 | 4092 54 | 16 | 3 |
| 1 | 4092 55 | 20 | 3 |
| 1 | 4092 56 | 25 | 3 |
| 1 | 4092 57 | 32 | 3 |
| 1 | 4092 58 | 40 | 3 |
| 1 | 4092 59 | 50 | 3 |
| 1 | 4092 60 | 63 | 3 |
| 1 | 4092 80 | 80 | 4-5 |
| 1 | 4092 81 | 100 | 4-5 |
| 1 | 4092 82 | 125 | 4-5 |
| Four pole 400 V~ | | | |
| 1 | 4093 29 | 1 | 4 |
| 1 | 4093 30 | 2 | 4 |
| 1 | 4093 31 | 3 | 4 |
| 1 | 4093 33 | 6 | 4 |
| 1 | 4093 34 | 10 | 4 |
| 1 | 4093 36 | 16 | 4 |
| 1 | 4093 37 | 20 | 4 |
| 1 | 4093 38 | 25 | 4 |
| 1 | 4093 39 | 32 | 4 |
| 1 | 4093 40 | 40 | 4 |
| 1 | 4093 41 | 50 | 4 |
| 1 | 4093 42 | 63 | 4 |
| 1 | 4093 62 | 80 | 6 |
| 1 | 4093 63 | 100 | 6 |
| 1 | 4093 64 | 125 | 6 |

MCBs DX³ 10000 - 16 kA **NEW**

thermal magnetic circuit breakers from 1 A to 125 A (continued)



4095 08

Dimensions **p. 65**
 Technical information **p. 59-60**

Conform to IEC 60898-1

Breaking capacity

10000 - IEC 60898-1 - 400 V~

16 kA - IEC 60947-2 - 400 V~

Can be equipped with DX³ auxiliaries and accessories **p. 58**

| Pack | Cat. Nos. | MCBs DX ³ 10000 - 16 kA - D curve | |
|-------------------------------|-----------|--|-------------------|
| Single pole 230/400 V~ | | | |
| | D curve | Nominal rating I _n (A) | Number of modules |
| 1 | 4094 25 | 2 | 1 |
| 1 | 4094 28 | 6 | 1 |
| 1 | 4094 30 | 10 | 1 |
| 1 | 4094 32 | 16 | 1 |
| 1 | 4094 33 | 20 | 1 |
| 1 | 4094 34 | 25 | 1 |
| 1 | 4094 35 | 32 | 1 |
| 1 | 4094 36 | 40 | 1 |
| 1 | 4094 37 | 50 | 1 |
| 1 | 4094 38 | 63 | 1 |
| Double pole 230/400 V~ | | | |
| 1 | 4094 44 | 2 | 2 |
| 1 | 4094 47 | 6 | 2 |
| 1 | 4094 49 | 10 | 2 |
| 1 | 4094 51 | 16 | 2 |
| 1 | 4094 52 | 20 | 2 |
| 1 | 4094 53 | 25 | 2 |
| 1 | 4094 54 | 32 | 2 |
| 1 | 4094 55 | 40 | 2 |
| 1 | 4094 56 | 50 | 2 |
| 1 | 4094 57 | 63 | 2 |
| 1 | 4094 58 | 80 | 3 |
| 1 | 4094 59 | 100 | 3 |
| 1 | 4094 60 | 125 | 3 |
| Triple pole 400 V~ | | | |
| 1 | 4094 92 | 2 | 3 |
| 1 | 4094 95 | 6 | 3 |
| 1 | 4094 97 | 10 | 3 |
| 1 | 4094 99 | 16 | 3 |
| 1 | 4095 00 | 20 | 3 |
| 1 | 4095 01 | 25 | 3 |
| 1 | 4095 02 | 32 | 3 |
| 1 | 4095 03 | 40 | 3 |
| 1 | 4095 04 | 50 | 3 |
| 1 | 4095 05 | 63 | 3 |
| 1 | 4095 06 | 80 | 4.5 |
| 1 | 4095 07 | 100 | 4.5 |
| 1 | 4095 08 | 125 | 4.5 |
| Four pole 400 V~ | | | |
| 1 | 4095 26 | 2 | 4 |
| 1 | 4095 29 | 6 | 4 |
| 1 | 4095 31 | 10 | 4 |
| 1 | 4095 33 | 16 | 4 |
| 1 | 4095 34 | 20 | 4 |
| 1 | 4095 35 | 25 | 4 |
| 1 | 4095 36 | 32 | 4 |
| 1 | 4095 37 | 40 | 4 |
| 1 | 4095 38 | 50 | 4 |
| 1 | 4095 39 | 63 | 4 |
| 1 | 4095 40 | 80 | 6 |
| 1 | 4095 41 | 100 | 6 |
| 1 | 4095 42 | 125 | 6 |

MCBs DX³ 6000 - 10 kA **NEW**

thermal magnetic circuit breakers from 1 A to 63 A



4079 65



4080 25

Dimensions **p. 65**
 Technical information **p. 59**

Conform to IEC 60898-1

Breaking capacity

6000 - IEC 60898-1 - 400 V~

10 kA - IEC 60947-2 - 400 V~

Can be equipped with DX³ auxiliaries and accessories **p. 58**

| Pack | Cat. Nos. | MCBs DX ³ 6000 - 10 kA - D curve | |
|-------------------------------|-----------|---|-------------------|
| Single pole 230/400 V~ | | | |
| | D curve | Nominal rating I _n (A) | Number of modules |
| 1 | 4079 63 | 1 | 1 |
| 1 | 4079 65 | 3 | 1 |
| 1 | 4079 66 | 4 | 1 |
| Double pole 230/400 V~ | | | |
| 1 | 4080 23 | 1 | 2 |
| 1 | 4080 25 | 3 | 2 |
| 1 | 4080 26 | 4 | 2 |
| Triple pole 400 V~ | | | |
| 1 | 4080 81 | 1 | 3 |
| 1 | 4080 83 | 3 | 3 |
| 1 | 4080 84 | 4 | 3 |

Auxiliaries and accessories **p. 58**



Download the full file at

<http://assets.kempstoncontrols.com/doc/Legrand%20Industrial%20and%20power%20protection%20catalogue.pdf>



KEMPSTON
CONTROLS