

# Hypra® IP 44 - ELV 16 A and LV 16 A

metal and plastic plugs and sockets



0520 22



0522 19



0522 44



0524 61



0520 82



0521 73 + 0522 89



0522 33 + 0522 39

Technical information and dimensions p. 165-167  
Conformity to International Standards p. 198

Conform to BS EN 60309-1, BS EN 60309-2, IEC 60309-1 and IEC 60309-2  
IP 44 according to BS EN 60529 and IEC 60529  
IK 09 plastic  
IK 10 metal according to BS EN 62262 and IEC 62262  
Self-extinguishing : 850 °C for insulated parts  
650 °C for housing - conforms to BS EN 60695-2-10 and IEC 60695-2-10  
Temp. rating : -50 °C to +100 °C  
Nickel plated brass contacts

## Pack Cat. Nos. Panel mounting sockets 16 A

Pack	ELV		Voltage
	Metal	Plastic	
5 1			20 to 25 V~
		0524 01	
		0524 02	2 P 3 P
			20 to 50 V~
1		0524 05	2 P
1	LV		100 to 130 V~
	Metal	Plastic	
	0519 30	0519 20	2 P + ⊥
			200 to 250 V~
1   5	0520 32	0520 22	2 P + ⊥
1	0520 33	0520 23	3 P + ⊥
1	0520 34	0520 24	3 P + N + ⊥
			380 to 415 V~
1   5	0522 33	0522 23	3 P + ⊥
1	0522 34	0522 24	3 P + N + ⊥
	Plastic modular		100 to 130 V~
1	0519 19		2 P + ⊥
			200 to 250 V~
5	0520 18		2 P + ⊥
1	0520 19		3 P + ⊥
			380 to 415 V~
5	0522 19		3 P + ⊥
1	0522 20		3 P + N + ⊥

## Mobile sockets 16 A

Pack	ELV		Voltage
	Metal	Plastic	
1			20 to 25 V~
1		0524 61	2 P
		0524 62	3 P
	LV		100 to 130 V~
	Plastic		
1	0519 80		2 P + ⊥
			200 to 250 V~
1	0520 82		2 P + ⊥
1	0520 83		3 P + ⊥
1	0520 84		3 P + N + ⊥
			380 to 415 V~
1	0522 83		3 P + ⊥
1	0522 84		3 P + N + ⊥

## Pack Cat. Nos. Straight plugs 16 A

Pack	ELV		Voltage
	Metal	Plastic	
5 1			20 to 25 V~
		0524 21	
		0524 22	2 P 3 P
			20 to 50 V~
1		0524 25	2 P
1	LV		100 to 130 V~
	Plastic		
	0519 40		2 P + ⊥
			200 to 250 V~
5	0520 42		2 P + ⊥
1	0520 43		3 P + ⊥
1	0520 44		3 P + N + ⊥
			380 to 415 V~
5	0522 43		3 P + ⊥
1	0522 44		3 P + N + ⊥

## Panel appliance inlets 16 A

Pack	LV		Voltage
	Metal	Plastic	
Covers available, see opposite			
1	Plastic		100 to 130 V~
	0519 70		
			2 P + ⊥
			200 to 250 V~
1	0521 72		2 P + ⊥
1	0520 73		3 P + ⊥
			380 to 415 V~
1	0521 73		3 P + ⊥
1	0521 74		3 P + N + ⊥

## Back boxes

Pack	Metal		Voltage
	Metal	Plastic	
<b>Surface mounting boxes</b>			
5	0524 19		For ELV 2 P / 3 P sockets
5	0520 29		For LV 16 A 2 P + ⊥ sockets
5	0522 39	0522 29	For LV 16 A 3 P + ⊥ / 3 P + N + ⊥ sockets
<b>Through entry surface mounting boxes</b>			
1	0520 89		For LV 16 A 2 P + ⊥ sockets
5	0522 89		For LV 16 A 3 P + ⊥ / 3 P + N + ⊥ sockets

## Appliance inlet covers

10	0521 25	For LV 16 A 2 P + ⊥ appliance inlets
5	0521 26	For LV 16 A 3 P + ⊥ appliance inlets
5	0521 27	For LV 16 A 3 P + N + ⊥ appliance inlets

## Hypra® IP 44 - LV 32 A

metal and plastic plugs and sockets



Technical information and dimensions **p. 165-167**  
Conformity to International Standards **p. 198**

Conform to BS EN 60309-1, BS EN 60309-2, IEC 60309-1 and IEC 60309-2  
IP 44 according to BS EN 60529 and IEC 60529  
IK 09 plastic  
IK 10 metal according to BS EN 62262 and IEC 62262  
Self-extinguishing : 850 °C for insulated parts  
650 °C for housing - conforms to BS EN 60695-2-10 and IEC 60695-2-10  
Temp. rating : -50 °C to +100 °C  
Nickel plated brass contacts

Pack	Cat. Nos.		Panel mounting sockets 32 A
	Metal	Modular	<b>200 to 250 V~</b>
1	0527 32	0527 18	2 P + ⊥
1	0527 33	0527 19	3 P + ⊥
			<b>380 to 415 V~</b>
1	0529 33	0529 19	3 P + ⊥
1	0529 34	0529 20	3 P + N + ⊥

Pack	Cat. Nos.	Mobile sockets 32 A
	Plastic	<b>200 to 250 V~</b>
1	0527 82	2 P + ⊥
1	0527 83	3 P + ⊥
		<b>380 to 415 V~</b>
1	0529 83	3 P + ⊥
1	0529 84	3 P + N + ⊥

Pack	Cat. Nos.	Straight plugs 32 A
	Plastic	<b>200 to 250 V~</b>
1	0527 42	2 P + ⊥
1	0527 43	3 P + ⊥
		<b>380 to 415 V~</b>
1	0529 43	3 P + ⊥
1	0529 44	3 P + N + ⊥


Pack	Cat. Nos.	Panel appliance inlets 32 A
	Plastic	Covers available, see below
		<b>200 to 250 V~</b>
1	0528 72	2 P + ⊥
		<b>380 to 415 V~</b>
1	0528 73	3 P + ⊥
1	0528 74	3 P + N + ⊥

Pack	Cat. Nos.	Back boxes
	Metal	<b>Surface mounting boxes</b>
1	0529 39	For LV 32 A 2 P + ⊥ / 3 P + ⊥ / 3 P + N + ⊥ sockets
	Plastic	<b>Through entry surface mounting boxes</b>
1	0529 90	For LV 32 A 2 P + ⊥ / 3 P + ⊥ / 3 P + N + ⊥ sockets

Pack	Cat. Nos.	Appliance inlet covers
5	0521 27	For LV 32 A 2 P + ⊥ / 3 P + ⊥ appliance inlets
5	0527 99	For LV 32 A 3 P + N + ⊥ appliance inlets

## Hypra® IP 44 - LV 63 A

metal and plastic plugs and sockets



Technical information and dimensions **p. 165-167**  
Conformity to International Standards **p. 198**

Conform to BS EN 60309-1, BS EN 60309-2, IEC 60309-1 and IEC 60309-2  
IP 44 according to BS EN 60529 and IEC 60529  
IK 09 plastic  
IK 10 metal according to BS EN 62262 and IEC 62262  
Self-extinguishing : 850 °C for insulated parts  
650 °C for housing - conforms to BS EN 60695-2-10 and IEC 60695-2-10  
Temp. rating : -50 °C to +100 °C  
Nickel plated brass contacts. 63 A units have a pilot pin

Pack	Cat. Nos.		Panel mounting sockets 63 A
	Metal	Plastic	<b>380 to 415 V~</b>
1	0538 33	0538 23	3 P + ⊥
1	0538 34	0538 24	3 P + N + ⊥

Pack	Cat. Nos.	Surface mounting socket 63 A
	Plastic	<b>380 to 415 V~</b>
1	0537 24	3 P + N + ⊥

Pack	Cat. Nos.	Mobile sockets 63 A
	Plastic	<b>380 to 415 V~</b>
1	0538 83	3 P + ⊥
1	0538 84	3 P + N + ⊥

Pack	Cat. Nos.	Straight plugs 63 A
	Plastic	<b>380 to 415 V~</b>
1	0538 43	3 P + ⊥
1	0538 44	3 P + N + ⊥

Pack	Cat. Nos.	Panel appliance inlets 63 A
	Plastic	<b>380 to 415 V~</b>
1	0537 73	3 P + ⊥
1	0537 74	3 P + N + ⊥

Pack	Cat. Nos.	Appliance inlet cover
5	0536 99	For LV 63 A 3 P + ⊥ / 3 P + N + ⊥ appliance inlets

Download the full file at

<http://assets.kempstoncontrols.com/doc/Legrand%20Industrial%20and%20power%20Protection%20catalogue.pdf>



**KEMPSTON**  
CONTROLS