


SWITCH DISCONNECTOR WITH FUSES

Model	
version	for NH C00
Design type	Basic version without handle
Fuse system	NH C00
Protection class	
Protection class IP	IP00
Dissipation	
Power loss [W]	
• maximum	142 W
Main circuit	
Operating voltage	
• rated value	690 V
• at AC / at 50/60 Hz / rated value	690 V
• at DC / rated value	220 V
Suitability for use	
• safety switch	Yes
Connections	
Type of connection, main circuit	busbar terminal
Type of electrical connection / for main current circuit	BUSBAR CONNECTION
Mechanical Design	
Height	105 mm
Width	142 mm
Depth	86.5 mm
Type of mounting	fixed mounted
Mounting type	Surface mounting and installation
Certificates	
Reference identifier / acc. to DIN EN 61346-2	Q
Declaration of Conformity	other
 EG-Konf.	
Environmental Confirmations	
Further information	

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3KL7113-4AA00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3KL7113-4AA00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3KL7113-4AA00

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>