

## Load break switch in metallic enclosure (cont.)

### ■ **SIRCO** in painted steel enclosure



#### General characteristics

- From 160 to 1600 A.
- 3 poles + solid neutral , 4 poles.
- Black lever (yellow/red on request).
- Triple lock in OFF position.
- Painted steel enclosure.
- Door latch system.
- Colour: RAL 7035.
- Cable gland plates: top and bottom.
- Degree of protection: IP65.
- Wall-mounted, 4 brackets included.

#### Accessories

- NO/NC auxiliary contact.
- Terminal screen.

#### References

Rating (A)	N° of poles	Handle Black Part number	Auxiliary contacts	Protective screen (top or bottom)	Enclosure		
					Size	H x W x D (mm)	Cable-in top and bottom (mm)
160	3 P + N	3032 <b>5016</b>	1 <sup>st</sup> NO/NC AC 2699 <b>0031</b>  2 <sup>nd</sup> 2NO/NC AC 2699 <b>0032</b>	2698 <b>3012</b>	CT 43	400 x 300 x 210	180 x 100
	4 P	3032 <b>4016</b>		2698 <b>4012</b>			
250	3 P + N	3032 <b>5025</b>		2698 <b>3020</b>			
	4 P	3032 <b>4025</b>		2698 <b>4020</b>			
400	3 P + N	3032 <b>5040</b>		2698 <b>3050</b>			
	4 P	3032 <b>4040</b>		2698 <b>4050</b>			
630	3 P + N	3032 <b>5063</b>		2698 <b>3050</b>			
	4 P	3032 <b>4063</b>		2698 <b>4050</b>			
800	3 P + N	3032 <b>5080</b>		2698 <b>3080</b>			
	4 P	3032 <b>4080</b>		2698 <b>4080</b>			
1250	3 P + N	3032 <b>5084</b>		2698 <b>3120</b>			
	4 P	3032 <b>4084</b>		2698 <b>4120</b>			
1600	3 P + N	3032 <b>5088</b>	2698 <b>3120</b>				
	4 P	3032 <b>4088</b>	2698 <b>4120</b>				
					CT 66	600 x 600 x 300	380 x 100
					CT 86	800 x 600 x 350	560 x 100
					CT 128	1200 x 800 x 300	660 x 100