

6000


**B & C**



2CSC400474F0201



2CSC400475F0201



2CSC400476F0201



2CSC400477F0201



**S 280 80-100A B characteristic**

Function: protection and control of the circuits against overloads and short-circuits; protection for people and big length cables in TN and IT systems.

Applications: commercial and industrial.

Standard: IEC/EN 60898, IEC/EN 60947-2

Icn=6 kA

Number of poles	Rated current	Order details	Bbn 8012542	Price 1 piece	Price group	Weight 1 piece	Pack unit
In A	Type code	Order code	EAN			kg	pc.
1	80	<b>S281 B80</b>	GHS2810001R0805	<b>499503</b>		0.140	1/6
	100	<b>S281 B100</b>	GHS2810001R0825	<b>499602</b>		0.140	1/6
2	80	<b>S282 B80</b>	GHS2820001R0805	<b>500100</b>		0.275	1/3
	100	<b>S282 B100</b>	GHS2820001R0825	<b>500209</b>		0.275	1/3
3	80	<b>S283 B80</b>	GHS2830001R0805	<b>500704</b>		0.400	1/2
	100	<b>S283 B100</b>	GHS2830001R0825	<b>500803</b>		0.400	1/2
4	80	<b>S284 B80</b>	GHS2840001R0805	<b>518006</b>		0.525	1
	100	<b>S284 B100</b>	GHS2840001R0825	<b>518105</b>		0.525	1

**S 280 80-100A C characteristic**

Function: protection and control of the circuits against overloads and short-circuits; protection for resistive and inductive loads with low inrush current.

Applications: commercial and industrial.

Standard: IEC/EN 60898, IEC/EN 60947-2

Icn=6 kA

Number of poles	Rated current	Order details	Bbn 8012542	Price 1 piece	Price group	Weight 1 piece	Pack unit
In A	Type code	Order code	EAN			kg	pc.
1	80	<b>S281 C80</b>	GHS2810001R0804	<b>499305</b>		0.140	1/6
	100	<b>S281 C100</b>	GHS2810001R0824	<b>499404</b>		0.140	1/6
2	80	<b>S282 C80</b>	GHS2820001R0804	<b>499909</b>		0.275	1/3
	100	<b>S282 C100</b>	GHS2820001R0824	<b>500001</b>		0.275	1/3
3	80	<b>S283 C80</b>	GHS2830001R0804	<b>500506</b>		0.400	1/2
	100	<b>S283 C100</b>	GHS2830001R0824	<b>500605</b>		0.400	1/2
4	80	<b>S284 C80</b>	GHS2840001R0804	<b>517801</b>		0.525	1
	100	<b>S284 C100</b>	GHS2840001R0824	<b>517900</b>		0.525	1