## EVS - Enhanced Visibility System


The EVS warning beacon provides a unique attention grabbing flickering light that has been developed to prevent acclimatisation. This beacon is effective in signalling extremely hazardous situations where there is a need for immediate action.


# CE

### **Technical Specification**

| Voltage      | 24Vdc            |
|--------------|------------------|
| Current      | 150mA            |
| Flash        | EVS              |
| Light Source | LED              |
| Temperature  | - 20°C to + 50°C |
| Protection   | IP65             |
| Construction | ABS, PC          |
| Weight       | 0.29Kg           |
| Colour       | Black base       |
| Lens Colour  | Red              |







#### **Features**

- Unique random flash pattern
- LED light source
- IP65 protection
- Locking lens

### **Benefits**

- Random flash has high attention grabbing properties
- Long life, low maintenance light source
- Suitable for external use
- Resists unauthorised access

| Reference          | Catalogue No.   | Description                      |
|--------------------|-----------------|----------------------------------|
| WB/L/R/024/EVS     | 755001FULL-0000 | LED EVS Beacon, 24Vdc, Red       |
| WB/L/A/024/EVS     | 755002FULL-0000 | LED EVS Beacon, 24Vdc, Amber     |
| WB/L/R/115-230/EVS | 755004FULL-0000 | LED EVS Beacon, 115-230Vac, Red  |
| WB/L/A/115-230/EVS | 755005FULL-0000 | LED EVS Beacon, 115-230Vac, Ambe |