



COORDINATE SWITCH, 22MM, ROUND,
 PLASTIC, BLACK,
 PLASTIC FRONT RING BLACK,
 4 SWITCH POSITIONS, MOMENTARY CONTACT,
 WITH MECHANICAL INTERLOCK IN O POSITION,
 WITH HOLDER, 1NO PER DIRECTION

Actuator:

Number of switching positions	4
Product equipment / integrated / neutral position	Yes

Front ring:

Product component / front ring	Yes
Material / of the front ring	plastic
Color / of the front ring	black

Auxiliary Contacts:

Number of NC contacts	0
Number of NO contacts	4
Number of change-over switches	0

General technical details:

Number of switching steps	4
---------------------------	---

Installation/mounting/dimensions:

Mounting diameter	mm	22
Mounting height	mm	82

Ambient conditions:

Protection class IP

IP65

Certificates/approvals:

General Product Approval

Test Certificates

other



CCC



GOST

[Special Test Certificate](#)

[Confirmation](#)

[other](#)

[Environmental Confirmations](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WWW/view/en/3SB1208-7JW01/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3SB1208-7JW01

last change:

Jan 21, 2013