


M 150/35.EE


Spacing 35 mm (1.38")
 Partition required
 see size on page 298



1 stud 25 x 3,15mm / 1"x.124" with
 - 2 screws HM10 for lug or bar
 - 1 central bolt HM8 for transversal connection

M 300/42.EE1


Spacing 42 mm (1.65")
 Partition required
 see size on page 298



1 stud 31,5 x 3,15mm / 1.24"x.124" with
 - 2 screws HM10 for lug or bar
 - 1 central bolt HM10 for transversal connection

M 185/42.EE

Spacing 42 mm (1.65")
 Partition required
 see size on page 298



1 stud 31,5 x 3,15mm / 1.24"x.124" with
 - 2 screws HM12 for lug or bar
 - 1 central bolt HM10 for transversal connection



Color	Type	Part number	Color	Type	Part number	Color	Type	Part number
Grey	M 150/35.EE	0115 156.17	Grey	M 300/42.EE1	0115 195.07	Grey	M 185/42.EE	0115 159.22

Characteristics

Wire size	DIN	NFC	UL	CSA
	Lug			
Bar	6-120 mm ²	10-95 mm ²	14-250 MCM	000 AWG max
Wire-clamp		25 x 3,15 mm	1" x .124"	
Voltage	IEC	IEC		
	V~ Without partition			
V~ With partition	1000	1000	600	600
Pulse	12 kV	12 kV		
Pollution degree	3	3		

Characteristics

Wire size	DIN	NFC	UL	CSA
	Lug	6-150 mm ²	10-150 mm ²	8-350 MCM
Bar		31,5 x 3,15 mm	1.24" x .124"	
Wire-clamp				
Voltage	IEC	IEC		
	V~ Without partition			
V~ With partition	1000	1000	600	600
Pulse	8 kV	8 kV		
Pollution degree	3	3		

Characteristics

Wire size	DIN	NFC	UL	CSA
	Lug	6-150 mm ²	10-150 mm ²	14-300 MCM
Bar		31,5 x 3,15 mm	1.24" x .124"	
Wire-clamp				
Voltage	IEC	IEC		
	V~ Without partition			
V~ With partition	1000	1000	600	600
Pulse	12 kV	12 kV		
Pollution degree	3	3		

Current	DIN	NFC		
Rated	232 A	192 A	255 A	270 A
Wire-size	232 A	192 A	255 A	270 A
Rated				
Lug	Central bolt	Wire-clamp	Wire stripping length	
H 16 mm	H 13 mm			
10 Nm 87 lb.in	6 Nm 52 lb.in			

Current	DIN	NFC		
Rated	269 A	269 A	310 A	310 A
Wire-size	120 mm ²	120 mm ²	350 MCM	250 MCM
Rated				
Lug	Central bolt	Wire-clamp	Wire stripping length	
H 16 mm	H 16 mm			
10 Nm 87 lb.in	10 Nm 87 lb.in			

Current	DIN	NFC		
Rated	269 A	269 A	285 A	310 A
Wire-size	120 mm ²	120 mm ²	300 MCM	250 MCM
Rated				
Lug	Central bolt	Wire-clamp	Wire stripping length	
H 18 mm	H 18 mm			
15,5 Nm 134 lb.in	10 Nm 87 lb.in			

Type	Part numbers
BAEH	th. 12 mm 0116 934.04
BADH	th. 12 mm 0116 900.27
BAMH	th. 9,1 mm 0114 836.00
ECS35	0168 841.03
BJS35	(25 x 3,15) 0168 868.16
BJS35	(25 x 3,15) 0168 869.17
CPU35	0116 514.07

Type	Part numbers
BAEH	th. 12 mm 0116 934.04
BADH	th. 12 mm 0116 900.27
BAMH	th. 9,1 mm 0114 836.00
ECS42	0168 843.05
BJS421	(31,5 x 3,15) 0168 870.14
BJS421	(31,5 x 3,15) 0168 871.01
CPU42	0116 515.00

Type	Part numbers
BAEH	th. 12 mm 0116 934.04
BADH	th. 12 mm 0116 900.27
BAMH	th. 9,1 mm 0114 836.00
ECS42	0168 843.05
BJS421	(31,5 x 3,15) 0168 870.14
BJS421	(31,5 x 3,15) 0168 871.01
CPU42	0116 515.00

(15) for ECS (6) for CPU

(15) for ECS (6) for CPU

(15) for ECS (6) for CPU