

Hypra® IP 66/67-55 - LV 16 A

plastic plugs and sockets



Technical information and dimensions **p. 171-173**
 Conformity to International Standards **p. 198**

Conform to BS EN 60309-1, BS EN 60309-2, IEC 60309-1 and IEC 60309-2
 IP according to BS EN 60529 and IEC 60529
 IK 09

Self-extinguishing : 850 °C for insulated parts, 650 °C for housing
 Stainless steel external screws - Nickel plated brass contacts
 Temp. rating : -50 °C to +100 °C

Pack	Cat. Nos.		Panel mounting sockets 16 A
1	Plastic	Modular	Plastic version can be used with back boxes to create surface mounting sockets (modular version is not compatible with back boxes)
5 1	0511 25	0511 46	100 to 130 V~ 2 P + ⊥
	0511 26	0511 46	200 to 250 V~ 2 P + ⊥
	0511 30	0511 50	380 to 415 V~ 3 P + ⊥
	0511 31	0511 51	3 P + N + ⊥

Pack	Cat. Nos.	Mobile sockets 16 A
1	0511 75	100 to 130 V~ 2 P + ⊥
1	0511 76	200 to 250 V~ 2 P + ⊥
		380 to 415 V~
1	0511 80	3 P + ⊥
1	0511 81	3 P + N + ⊥

Pack	Cat. Nos.	Straight plugs 16 A
1	0511 55	100 to 130 V~ 2 P + ⊥
1	0511 56	200 to 250 V~ 2 P + ⊥
		380 to 415 V~
5	0511 60	3 P + ⊥
5	0511 61	3 P + N + ⊥

Pack	Cat. Nos.	Angled plugs 16 A
1	0511 06	200 to 250 V~ 2 P + ⊥
		380 to 415 V~
1	0511 10	3 P + ⊥
1	0511 11	3 P + N + ⊥

Pack	Cat. Nos.	Back boxes
		Surface mounting boxes
5	0520 29	For LV 16 A 2 P + ⊥ sockets
5	0522 29	For LV 16 A 3 P + ⊥ / 3 P + N + ⊥ sockets
		Through entry surface mounting boxes
1	0520 89	For LV 16 A 2 P + ⊥ sockets
5	0522 89	For LV 16 A 3 P + ⊥ / 3 P + N + ⊥ sockets

Hypra® IP 66/67-55 - LV 32 A

plastic plugs and sockets



0530 50 + 0529 40

Technical information and dimensions **p. 171-173**
Conformity to International Standards **p. 198**

Conform to BS EN 60309-1, BS 60309-2, IEC 60309-1 and IEC 60309-2
IP according to BS EN 60529 and IEC 60529

IK 09
Self-extinguishing : 850 °C for insulated parts, 650 °C for housing
Stainless steel external screws - Nickel plated brass contacts
Temp. rating : -50 °C to +100 °C

Pack Cat. Nos. Panel mounting sockets (modular) 32 A

Pack	Cat. Nos.	200 to 250 V~	380 to 415 V~
1	Modular 0530 46	2 P + ⊥	
1	0530 50	3 P + ⊥	
1	0530 51	3 P + N + ⊥	

Mobile sockets 32 A

Pack	Cat. Nos.	200 to 250 V~	380 to 415 V~
1	0530 76	2 P + ⊥	
1	0530 80	3 P + ⊥	
1	0530 81	3 P + N + ⊥	

Straight plugs 32 A

Pack	Cat. Nos.	200 to 250 V~	380 to 415 V~
1	0530 56	2 P + ⊥	
1	0530 60	3 P + ⊥	
1	0530 61	3 P + N + ⊥	

Angled plugs 32 A

Pack	Cat. Nos.	200 to 250 V~	380 to 415 V~
1	0530 06	2 P + ⊥	
1	0530 10	3 P + ⊥	
1	0530 11	3 P + N + ⊥	

Back boxes

Pack	Cat. Nos.	Surface mounting boxes	Through entry surface mounting boxes
1	0529 40	For LV 32 A 2 P + ⊥ / 3 P + ⊥ / 3 P + N + ⊥ sockets	
1	0529 90		For LV 32 A 2 P + ⊥ / 3 P + ⊥ / 3 P + N + ⊥ sockets

Hypra® IP 66/67-55 - LV 63 and 125 A

plastic plugs and sockets



0594 27



0595 32

Technical information and dimensions **p. 171-173**
Conformity to International Standards **p. 198**

Conform to BS EN 60309-1, BS 60309-2, IEC 60309-1 and IEC 60309-2
IP according to BS EN 60529 and IEC 60529

IK 09
Self-extinguishing : 850 °C for insulated parts, 650 °C for housing
Stainless steel external screws - Nickel plated brass contacts
Temp. rating : -50 °C to +100 °C
LV 63 A and 125 A have a pilot pin

Pack Cat. Nos. Panel mounting sockets 63 and 125 A

Pack	Cat. Nos.		380 to 415 V~
	63 A	125 A	
1	0594 27	0595 12	3 P + ⊥
1	0594 28	0595 13	3 P + N + ⊥

Surface mounting sockets 63 and 125 A

Pack	Cat. Nos.		380 to 415 V~
	63 A	125 A	
1	0594 37	0595 02	3 P + ⊥
1	0594 38	0595 03	3 P + N + ⊥

Mobile sockets 63 and 125 A

Pack	Cat. Nos.		380 to 415 V~
	63 A	125 A	
1	0594 87	0595 32	3 P + ⊥
1	0594 88	0595 33	3 P + N + ⊥

Straight plugs 63 and 125 A

Pack	Cat. Nos.		380 to 415 V~
	63 A	125 A	
1	0594 47	0595 22	3 P + ⊥
1	0594 48	0595 23	3 P + N + ⊥

Download the full file at

<http://assets.kempstoncontrols.com/doc/Legrand%20Industrial%20and%20power%20protection%20catalogue.pdf>



KEMPSTON
CONTROLS