

# power contactors CX<sup>3</sup> with handle

from 16 A to 63 A



4 125 44



4 125 56

Dimensions **see e-catalogue**  
 Technical characteristics **p. 86**

Conform to IEC/EN 61095  
 Space for power supply busbar on top (up to 25 A)

| Pack | Cat.Nos               | <b>Power contactors with 24 V<sup>~</sup> coil and handle</b>   |            |                 |                   |
|------|-----------------------|---|------------|-----------------|-------------------|
|      |                       | Manual override for test and repair function, carried out via the handle<br>Permanent "ON" or "OFF" without automatic reset |            |                 |                   |
|      |                       | <b>2-pole - 250 V<sup>~</sup></b>   |            |                 |                   |
| 1    | 4 125 14              | I max   | Connection | Type of contact | Number of modules |
| 1    | 4 125 15 <sup>1</sup> | 25 A  |            | 2 N/O           | 1                 |
| 1    | 4 125 16 <sup>1</sup> | 40 A  |            | 2 N/O           | 2                 |
|      |                       | 63 A  |            | 2 N/O           | 2                 |
|      |                       | <b>4-pole - 400 V<sup>~</sup></b>   |            |                 |                   |
| 1    | 4 125 17              | 25 A  |            | 4 N/O           | 2                 |
| 1    | 4 125 18 <sup>1</sup> | 40 A  |            | 4 N/O           | 3                 |
| 1    | 4 125 19 <sup>1</sup> | 63 A  |            | 4 N/O           | 3                 |

| Pack | Cat.Nos               | <b>Low noise power contactors with 230 V<sup>~</sup> coil and handle</b> |            |                 |                   |
|------|-----------------------|--|------------|-----------------|-------------------|
|      |                       | <b>2-pole - 250 V<sup>~</sup></b>  |            |                 |                   |
| 1    | 4 125 58              | I max  | Connection | Type of contact | Number of modules |
| 1    | 4 125 59 <sup>1</sup> | 25 A   |            | 2 N/O           | 1                 |
| 1    | 4 125 60 <sup>1</sup> | 40 A   |            | 2 N/O           | 2                 |
|      |                       | 63 A   |            | 2 N/O           | 2                 |
|      |                       | <b>4-pole - 400 V<sup>~</sup></b>  |            |                 |                   |
| 1    | 4 125 61              | 25 A   |            | 4 N/O           | 1                 |
| 1    | 4 125 62 <sup>1</sup> | 40 A   |            | 4 N/O           | 2                 |
| 1    | 4 125 63 <sup>1</sup> | 63 A   |            | 4 N/O           | 2                 |

| Pack | Cat.Nos               | <b>Power contactors with 230 V<sup>~</sup> coil and handle</b>   |            |                 |                   |
|------|-----------------------|--|------------|-----------------|-------------------|
|      |                       | Manual override for test and repair function, carried out via the handle<br>Permanent "ON" or "OFF" without automatic closing of the contactor |            |                 |                   |
|      |                       | <b>2-pole - 250 V<sup>~</sup></b>  |            |                 |                   |
| 4    | 4 125 44              | I max  | Connection | Type of contact | Number of modules |
| 1    | 4 125 45 <sup>1</sup> | 25 A   |            | 2 N/O           | 1                 |
| 1    | 4 125 47 <sup>1</sup> | 40 A   |            | 2 N/O           | 2                 |
|      |                       | 63 A   |            | 2 N/O           | 2                 |
| 1    | 4 125 48 <sup>1</sup> | 63 A   |            | 2 N/C           | 2                 |
|      |                       | <b>3-pole 400 V<sup>~</sup></b>  |            |                 |                   |
| 1    | 4 125 49 <sup>1</sup> | 40 A   |            | 3 N/O           | 3                 |
| 1    | 4 125 50 <sup>1</sup> | 63 A   |            | 3 N/O           | 3                 |
|      |                       | <b>4-pole 400 V<sup>~</sup></b>  |            |                 |                   |
| 2    | 4 125 51              | 25 A   |            | 4 N/O           | 2                 |
| 1    | 4 125 53 <sup>1</sup> | 40 A   |            | 4 N/O           | 3                 |
| 1    | 4 125 56 <sup>1</sup> | 63 A   |            | 4 N/O           | 3                 |
| 1    | 4 125 57 <sup>1</sup> | 63 A   |            | 4 N/C           | 3                 |

1: Handle can be accessed after removing blanking plate