

Synergy® metalclad

switches and socket outlets



Finish : grey epoxy coated steel
Terminal screws captive and backed off ready for cabling
Supplied complete with close fit surface mounting back box with knockouts

| Pack | Cat. Nos. | Single pole plate switches 10 AX - 250 V \sim |
|------|-----------|---|
| | | Conform to BS EN 60669-1 : 2000 Nominal dimensions : 86 x 86 x 43 mm |
| 5 | 7338 00 | 1 gang – 1 way 1 gang – 2 way 1 gang – intermediate |
| 5 | 7338 01 | |
| 5 | 7338 05 | |
| 5 | 7338 02 | 2 gang – 2 way |
| 5 | 7338 03 | 3 gang – 2 way |
| | | Double pole socket outlets 13 A - 250 V\sim |
| | | Conform to BS 1363 - Part 2 : 1995 2 earth terminals Nominal dimensions : 86 x 86 x 43 mm |
| 5 | 7338 60 | 1 gang – switched |
| 5 | 7338 61 | 1 gang – switched + red LED power indicator Nominal dimensions : 86 x 146 x 43 mm |
| 5 | 7338 70 | 2 gang – switched |
| 5 | 7338 71 | 2 gang – switched + red LED power indicator |

Unswitched and key switched socket outlets 13 A - 250 V \sim

| Pack | Cat. Nos. | Unswitched and key switched socket outlets 13 A - 250 V \sim |
|------|-----------|---|
| | | Conform to BS 1363 - Part 2 : 1995 2 earth terminals Nominal plate dimensions : 1 gang - 86 x 86 mm 2 gang - 86 x 146 mm |
| 10 | 7338 65 | 1 gang – unswitched |
| 5 | 7338 75 | 2 gang – unswitched |
| 1 | 8200 73 | 2 gang single socket with DP key switch |

Socket outlets 15 A - 250 V \sim

| Pack | Cat. Nos. | Socket outlets 15 A - 250 V \sim |
|------|-----------|--|
| | | Conform to BS 546 : 1950 Nominal dimensions : 86 x 86 x 43 mm |
| 5 | 7338 88 | 1 gang – unswitched |
| 5 | 7338 89 | 1 gang – switched |

RCD sockets 13 A - 250 V \sim

Conform to BS 7288 : 1990 and BS 1363 - Part 2 : 1995
Conventional earth pin release shutter
Maximum operating current 16 A Electronic RCD module with a membrane switch for "test and reset"
Flush mounting back box : min. 25 mm deep

| Pack | Cat. Nos. | RCD sockets 13 A - 250 V \sim |
|------|-----------|--|
| | | ELO - DP 30 mA - active Trips in the event of a power failure Ideal for applications where it is desirable to prevent automatic reactivation of equipment after a power failure. For hazardous, e.g. machinery, power tools |
| 1 | 7338 80 | 1 gang Nominal plate dimensions : 86 x 86 mm |
| 1 | 7338 82 | 2 gang Nominal plate dimensions : 86 x 146 mm |
| | | ELR - DP 30 mA - passive Trips in the event of a power failure Ideal for applications where it is desirable to automatically re-activate equipment after a power failure. E.g. fridge, freezer, unmanned areas |
| 1 | 7338 81 | 1 gang Nominal plate dimensions : 86 x 86 mm |
| 1 | 7338 83 | 2 gang Nominal plate dimensions : 86 x 146 mm |

Surface mounting back boxes with or without knockouts
p. 60



Synergy® metalclad

fused connection units and control switches



Finish : grey epoxy coated steel
Terminal screws captive and backed off ready for cabling
Supplied complete with close fit surface mounting back box with knockouts

| Pack | Cat. Nos. | Fused connection units 13 A - 250 V~ |
|------|-----------|--|
| | | Conform to BS 1363 - Part 4 : 1995 Fused 13 A (fuse supplied) Fuse drawer retained by quarter turn catch, drawer padlockable in open position for safety Nominal dimensions : 86 x 86 x 43 mm |
| | | Switched |
| 5 | 7338 34 | Switched, DP |
| 5 | 7338 35 | Switched, DP with red LED power indicator |
| 5 | 7338 36 | Switched, DP with cord outlet |
| 5 | 7338 37 | Switched, DP with cord outlet + red LED power indicator |
| | | Unswitched |
| 5 | 7338 30 | Unswitched |
| 5 | 7338 31 | Unswitched with red LED power indicator |
| 5 | 7338 32 | Unswitched with cord outlet |
| 5 | 7338 33 | Unswitched with cord outlet + red LED power indicator |

| Pack | Cat. Nos. | Double pole switches 20 A - 250 V~ |
|------|-----------|--|
| | | Conform to BS EN 60669-1 : 2000 Nominal dimensions : 86 x 86 x 43 mm |
| 5 | 7338 10 | 20 A DP |
| 5 | 7338 14 | 20 A DP with cord outlet |
| 5 | 7338 16 | 20 A DP with cord outlet + red LED power indicator |
| 5 | 7338 12 | 20 A DP + red LED power indicator |
| | | Cable outlet 20 A - 250 V~ |
| | | Conforms to BS 5733 : 1995 Nominal dimensions : 86 x 86 x 43 mm |
| 5 | 7338 19 | 20 A – with terminal block and outlet gland |
| | | Double pole switches 45 A - 250 V~ |
| | | Conform to BS EN 60669-1 : 2000 Red rocker Nominal dimensions : 146 x 86 x 43 mm |
| 5 | 7338 20 | 45 A DP |
| 5 | 7338 21 | 45 A DP + red LED power indicator |

Surface mounting back boxes with or without knockouts
p. 60



Download the full file at

<http://assets.kempstoncontrols.com/doc/Synergy%20Wiring%20Accessories.pdf>



KEMPSTON
CONTROLS