


modular fuse carriers and device accessories



4049 05



4049 26



0016 91



0016 90

| Pack | Cat. Nos. | Modular fuse carrier accessory |
|------|-----------|----------------------------------------------|
| 3 | 0057 99 | Padlock support suitable for Ø 5 mm padlocks |

| Pack | Cat. Nos. | Modular device accessories | |
|------|-----------|-------------------------------------------------------------------------------------------------------------------------|--|
| 10 | 4063 07 | Spacing elements For heat reduction - 0-5 module | |
| 2 | 4063 03 | Locking device Attachment for Ø 5 mm padlocks for DX ³ | |
| 3 | 4063 13 | Padlock Ø 5 mm | |
| 20 | 4049 05 | Entry terminals Accepts conductors 4-25 mm ² max for single pole busbars only IP 2X | |
| 20 | 4049 06 | Accepts conductors 6-35 mm ² max | |
| 20 | 4049 26 | Supply busbars For 13 single pole units ¹ Reversible blue/black | |
| 10 | 4049 37 | For 57 single pole units ¹ Reversible blue/black | |
| 5 | 4049 38 | For 6 double pole units ^{2,3} | |
| 10 | 4049 39 | For 28 double pole units ^{2,3} | |
| 5 | 4049 42 | For 4 triple pole units ^{2,3} | |
| 10 | 4049 43 | For 19 triple pole units ^{2,3} | |
| 3 | 4049 44 | For 3 four pole units ^{2,3} | |
| 20 | 4049 88 | Insulation shroud For non-utilised busbar prongs | |
| 10 | 0049 96 | Self-adhesive label holder Width : 16 mm Width available for marking : 12 mm Length 430 mm (24 modules) | |
| 10 | 0016 65 | Grey blanking plate RAL 7035 18 module, blanking strip | |

1 : 16 mm² section rated at 80 A with central feed
2 : 10 mm² section rated at 63 A with central feed
3 : With insulated ends

| Pack | Cat. Nos. | Modular device accessories (continued) |
|------|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 5 | 0016 91 | Protective terminal shield Light grey Ensures the protection of wiring and terminals in modular mechanisms fitted in enclosures (Atlantic or Marina) Width 45 mm, Length 1 m Clips on to support 0016 90 (below) |
| 10 | 0016 90 | Insulated support For protective terminal shield Clips on to rail EN 60715 |

DX³ MCBs p. 56-57



Enclosures p. 14-23



cylindrical cartridge fuses

HRC



Dimensions p. 79

Numbers refer to physical size of fuse i.e. 10 x 38 means Ø 10 mm x 38 mm length

| Pack | Cat. Nos. | Miniature type 5 x 20 | | |
|------|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|--------------------------|
| | | Type F (fast acting) fuse Ceramic body Conform to IEC 60127-2 For use with transformers (see p. 90), Viking 3 terminals (see p. 118) etc. | | |
| | | Rating (Amps) | Voltage ~ (Volts) | Breaking capacity (Amps) |
| 10 | 0102 02 | 0.2 | | |
| 10 | 0102 05 | 0.5 | | |
| 10 | 0102 06 | 0.63 | | |
| 10 | 0102 10 | 1 | | |
| 10 | 0102 12 | 1.25 | | |
| 10 | 0102 16 | 1.6 | | |
| 10 | 0102 20 | 2 | 250 | 1 500 |
| 10 | 0102 25 | 2.5 | | |
| 10 | 0102 30 | 3.15 | | |
| 10 | 0102 50 | 5 | | |
| 10 | 0102 63 | 6.3 | | |
| 10 | 0102 96 ¹ | 10 | 250 | 500 |

| Pack | Cat. Nos. | Type gG | | |
|------|-----------|------------------------------------------------------------------|-------------------|--------------------------|
| | | Conform to BS EN 60269-1, IEC 60269-1 Bureau Veritas approved | | |
| | | Rating (Amps) | Voltage ~ (Volts) | Breaking capacity (Amps) |
| | | Without indicator | | |
| | | 8 x 32 | | |
| 10 | 0123 01 | 1 | | |
| 10 | 0123 02 | 2 | | |
| 10 | 0123 04 | 4 | | |
| 10 | 0123 06 | 6 | | |
| 10 | 0123 08 | 8 | 400 | 20 000 |
| 10 | 0123 10 | 10 | | |
| 10 | 0123 12 | 12 | | |
| 10 | 0123 16 | 16 | | |

1 : Overrating not described by standards

| Pack | Cat. Nos. | Type gG industrial | | |
|------|-----------|------------------------------------------------------------------------------------------------------------------------------|-------------------|--------------------------|
| | | HRC (high rupturing capacity) Conform to BS EN 60269-1 and 2 (BS 88) IEC 60269-1, 2 and 2-1 Bureau Veritas approved | | |
| | | Rating (Amps) | Voltage ~ (Volts) | Breaking capacity (Amps) |
| | | Without indicator | | |
| | | 10 x 38 | | |
| 10 | 0133 94 | 0.5 | | |
| 10 | 0133 01 | 1 | | |
| 10 | 0133 02 | 2 | | |
| 10 | 0133 04 | 4 | | |
| 10 | 0133 06 | 6 | 500 | 100 000 |
| 10 | 0133 08 | 8 | | |
| 10 | 0133 10 | 10 | | |
| 10 | 0133 12 | 12 | | |
| 10 | 0133 16 | 16 | | |
| 10 | 0133 20 | 20 | | |
| 10 | 0133 25 | 25 | | |
| | | Without striker | | |
| | | 14 x 51 | | |
| 10 | 0143 02 | 2 | | |
| 10 | 0143 04 | 4 | | |
| 10 | 0143 06 | 6 | | |
| 10 | 0143 10 | 10 | 500 | 100 000 |
| 10 | 0143 16 | 16 | | |
| 10 | 0143 20 | 20 | | |
| 10 | 0143 25 | 25 | | |
| 10 | 0143 32 | 32 | | |
| 10 | 0143 40 | 40 | | |
| 10 | 0143 50 | 50 | | |
| | | Without striker | | |
| | | 22 x 58 | | |
| 10 | 0153 10 | 10 | | |
| 10 | 0153 16 | 16 | | |
| 10 | 0153 20 | 20 | | |
| 10 | 0153 25 | 25 | 500 | 100 000 |
| 10 | 0153 32 | 32 | | |
| 10 | 0153 40 | 40 | | |
| 10 | 0153 50 | 50 | | |
| 10 | 0153 63 | 63 | | |
| 10 | 0153 80 | 80 | | |
| 10 | 0153 96 | 100 | 400 | |
| 10 | 0153 97 | 125 | | |

| Pack | Cat. Nos. | Neutral links | |
|------|-----------|---------------|--|
| 10 | 0123 00 | 8 x 32 | |
| 10 | 0133 00 | 10 x 38 | |
| 10 | 0143 00 | 14 x 51 | |
| 10 | 0153 00 | 22 x 58 | |

High breaking capacity suits industrial applications



Download the full file at

<http://assets.kempstoncontrols.com/doc/Legrand%20Industrial%20and%20power%20protection%20catalogue.pdf>



KEMPSTON
CONTROLS