

## Datasheet - KA-0804

Connector / Connector M12 / KA-08


 Preferred typ


- for Transmitter
- Pre-wired cable
- 4-pole
- for SLC/SLG

(Minor differences between the printed image and the original product may exist!)

### Ordering details

Product type description	KA-0804
Article number	101207741
EAN Code	4030661378879
eCl@ss	

### Global Properties

Permanent light	Anschlussleitung KA-08
Versions	Pre-wired cable
Materials	
- Material of the housings	Plastic
- Material of the nuts	Metal film, , nickel-plated
- Material of the cable mantle	PVC
- Material of the contacts	Metal film, , gold-plated
Connector	female connector
Design	straight
Colouring	
- Enclosure color	Black
- Cable colour	Grey
Weight	200

### Mechanical data

Connection type	Screw connection
termination	M12
Bolting device	Screw locking
Cable length	5

Conductors	4 x 0,34
Mechanical life	100 cycles
Min. bending radius	

### Ambient conditions

---

Ambient temperature	
- Min. environmental temperature	-30 Connector -40 cable
- Max. environmental temperature	+90 Connector +80 cable
Protection class	IP67
Degree of pollution	3

### Electrical data

---

Number of poles	4
Number of cores	4
Contact load capacity	4 A
contact resistance	≤ 5
Rated operating voltage	250

### LED switching conditions display

---

LED switching conditions display (Y/N)	No
--	----


### Pin assignment

---

1	brown
2	white
3	blue
4	black

### Images

---



Contact arrangement