

# Synergy® white

## socket outlets (continued)



7300 90



6781 38



7300 89



7300 69



7300 59

Front plates : white thermoset  
Terminal screws captive and backed off ready for cabling  
Supplied with faceplate screw caps

Pack	Cat. Nos.	Shaver socket
1	7300 90	<p>Conforms to BS EN 61558-2-5 : 1998 IP 24</p> <p>For use with European, British, American and Australian 2 pin plugs Screwless live and neutral terminals Double wound isolating transformer Automatic self-resetting overload feature Plug insertion operates microswitch which energises transformer Flush mounting back box : min. 47 mm deep Nominal plate dimensions : 146 x 86 mm</p> <p>Supply : 230 V - 50/60 Hz Output : 230/120 V - 20 VA max.</p>

Pack	Cat. Nos.	Socket outlets 15 A - 250 V~
		<p>Conform to BS 546 : 1950 Optional red LED 'power on' upgrade pack available Flush mounting back box : min. 35 mm deep Nominal plate dimensions : 86 x 86 mm</p>
10	7300 88	1 gang – unswitched
10	7300 89	1 gang – switched

Pack	Cat. Nos.	RCD sockets 13 A - 250 V~
		<p>Conform to BS 7288 : 1990 and BS 1363 - Part 2 : 1995 Terminal screws captive and backed off ready for cabling Conventional earth pin release shutter Maximum operating current 16 A Incorporate a "test and reset" button Flush mounting back box : min. 25 mm deep Nominal plate dimensions : - 1 gang 86 x 86 mm - 2 gang 86 x 146 mm</p>
		<p><b>ELO - DP 30 mA - active</b> - trips in the event of a power failure - suitable in applications where automatic restoration of supply would be hazardous, e.g. machinery, power tools</p>
1	6781 33	RCD unit 1 gang DP 30 mA active
1	6781 37	RCD unit 2 gang DP 30 mA active
		<p><b>ELR - DP 30 mA - passive</b> - does not trip in the event of a power failure - suitable in applications where automatic restoration of supply is required, e.g. fridge, freezer, unmanned areas</p>
1	6781 34	RCD unit 1 gang DP 30 mA passive
1	6781 38	RCD unit 2 gang DP 30 mA passive

Pack	Cat. Nos.	Socket outlets 5 A - 250 V~
		<p>Conform to BS 546 : 1950 Optional red LED 'power on' upgrade pack available 2 earth terminals Flush mounting back box : min. 25 mm deep Nominal plate dimensions : 86 x 86 mm</p>
10	7300 68	1 gang – unswitched
10	7300 69	1 gang – switched

Pack	Cat. Nos.	Socket outlet 2 A - 250 V~
		<p>Conforms to BS 546 : 1950 Optional red LED 'power on' upgrade pack available Conventional earth pin shutter release Flush mounting back box : min. 25 mm deep Nominal plate dimensions : 86 x 86 mm</p>
10	7300 59	1 gang – unswitched

**For switched USB socket outlets  
Contact us on +44 (0) 345 605 4333**

**Red power indicator LED pack p.38**

Flush and surface mounting  
back boxes p. 39



# Synergy® white

## fused connection units



7300 34



7300 35 + optional red LED power indicator (Cat. No. 7301 58)



7300 30



Bespoke and standard engraving available **p. 41**



7300 36



7301 36



7300 33

Front plates : white thermoset  
Terminal screws captive and backed off ready for cabling  
Supplied with faceplate screw caps

Pack	Cat. Nos.	Fused connection units 13 A - 250 V~
		<p>Conform to BS 1363 - Part 4 : 1995</p> <p>Options available as standard with red 'power on' LED indicator</p> <p>LED 'power on' upgrade pack also available Fused 13 A (fuse supplied)</p> <p>Fuse drawer retained by quarter turn catch, drawer padlockable in open position for safety</p> <p>To obtain flush to wall external cord connection on standard depth Cat. Nos. use cord outlet accessory box Cat. No. 7300 53 <b>p. 38</b></p> <p>Flush mounting back box : min. 25 mm deep</p> <p>Nominal plate dimensions : 86 x 86 mm</p> <p><b>Switched</b></p>
10	7300 34	Switched, DP
10	7300 35	Switched, DP with red LED power indicator
10	7300 36	Switched, DP with cord outlet
10	7300 37	Switched, DP with cord outlet + red LED power indicator
10	7301 36	Switched, DP - deep plate with bottom cord outlet

**Red power indicator LED pack p.38**

Pack	Cat. Nos.	Fused connection units 13 A - 250 V~ (continued)
		<b>Unswitched</b>
10	7300 30	Unswitched
10	7300 31	Unswitched with red LED power indicator
10	7300 32	Unswitched with cord outlet
10	7300 33	Unswitched with cord outlet + red LED power indicator

**Red power indicator LED pack p.38**

Flush and surface mounting back boxes **p. 39**



Download the full file at

<http://assets.kempstoncontrols.com/doc/Synergy%20Wiring%20Accessories.pdf>



**KEMPSTON**  
CONTROLS