

SWITCH DISCONNECTOR WITH FUSES



Model	
version	for NH 3
Design type	Basic version without handle
Fuse system	NH 3
Protection class	
Protection class IP	IP00
Dissipation	
Power loss [W]	
• maximum	356 W
Main circuit	
Operating voltage	
• rated value	690 V
• at AC / at 50/60 Hz / rated value	690 V
• at DC / rated value	220 V
Suitability for use	
• safety switch	Yes
Connections	

Type of connection, main circuit	busbar terminal
Type of electrical connection / for main current circuit	BUSBAR CONNECTION

Mechanical Design	
Height	286 m
Width	356 m
Depth	164 m
Type of mounting	fixed mounted
Mounting type	Surface mounting and installation

Environmental conditions	
<b>Ambient temperature</b>	
• during operation / minimum	-20 °C
• during operation / maximum	45 °C

Certificates	
Reference identifier / acc. to DIN EN 61346-2	Q

<b>Declaration of Conformity</b>	<b>other</b>
----------------------------------	--------------



[Environmental Confirmations](#)

### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3KL7151-3AA00>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3KL7151-3AA00>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3KL7151-3AA00](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3KL7151-3AA00)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>

