

PNOZ X4 110VAC 3n/o 1n/c

774734



Safety relay (standalone) Inputs: 1-/2-channel wiring with/without detection of shorts across contacts Outputs: 3 N/O, 1 N/C. Automatic/monitored start UB 110 V DC, width: 45 mm, plug-in terminals of screw type Monitoring E-STOP, safety gates.

Technical details

Approvals:	CE;cULus Listed;EAC (Eurasian);TÜV;CCC
Application options:	Safety gate monitor;Instantaneous E-STOP monitoring;Light beam device mon. Type 4;Light beam device mon. Type 2 w/o t/p;Light beam device mon. Type 2 with t/p
Operating modes:	Single-channel;Automatic reset;Dual-channel;Manual reset;Detection of shorts across contacts;Monitored manual reset;without detection of shorts across contacts
Product standard:	EN 60947-5-1
Standards:	EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1
Supply voltage (V):	110,0
Supply voltage type:	AC
Terminal style:	fixed
Terminal type:	Screw terminal
Number of instantaneous safety contacts:	3
Number of auxiliary contacts:	1
Stop category:	0
Max. current at DC13 I (6 cycles/min):	7.0 A
Max. current at AC15:	5.0 A
Width dimension:	45.0 mm
Height dimension:	87.0 mm
Depth dimension:	121.0 mm
Gross weight:	380 g

Net weight:	370 g
Ambient temperature:	-10 - 55 °C

Optional accessories



774090

COVER P-93