

# MCBs DX<sup>3</sup> 10000 - 16 kA

**NEW**

thermal magnetic circuit breakers from 1 A to 125 A



4088 69



4089 43



4091 11



4092 03

Dimensions **p. 65**  
 Technical information **p. 59-60**

Conform to IEC 60898-1

Breaking capacity

10000 - IEC 60898-1 - 400 V~

16 kA - IEC 60947-2 - 400 V~

Can be equipped with DX<sup>3</sup> auxiliaries and accessories **p. 58**

**MCBs DX<sup>3</sup> 10000 - 16 kA - B curve**

Pack	Cat. Nos.	Nominal rating I <sub>n</sub> (A)	Number of modules
<b>Single pole 230/400 V~</b>			
B curve			
1	4088 65	1	1
1	4088 66	2	1
1	4088 67	3	1
1	4088 69	6	1
1	4088 70	10	1
1	4088 72	16	1
1	4088 73	20	1
1	4088 74	25	1
1	4088 75	32	1
1	4088 76	40	1
1	4088 78	63	1
<b>Double pole 230/400 V~</b>			
1	4089 35	1	2
1	4089 36	2	2
1	4089 37	3	2
1	4089 39	6	2
1	4089 40	10	2
1	4089 42	16	2
1	4089 43	20	2
1	4089 44	25	2
1	4089 45	32	2
1	4089 46	40	2
1	4089 48	63	2
<b>Triple pole 400 V~</b>			
1	4089 84	1	3
1	4089 85	2	3
1	4089 86	3	3
1	4089 88	6	3
1	4089 89	10	3
1	4089 91	16	3
1	4089 92	20	3
1	4089 93	25	3
1	4089 94	32	3
1	4089 95	40	3
1	4089 96	50	3
1	4089 97	63	3
<b>Four pole 400 V~</b>			
1	4090 58	1	4
1	4090 62	6	4
1	4090 63	10	4
1	4090 65	16	4
1	4090 66	20	4
1	4090 67	25	4
1	4090 68	32	4
1	4090 69	40	4
1	4090 70	50	4
1	4090 71	63	4

**MCBs DX<sup>3</sup> 10000 - 16 kA - C curve**

Pack	Cat. Nos.	Nominal rating I <sub>n</sub> (A)	Number of modules
<b>Single pole 230/400 V~</b>			
C curve			
1	4091 07	1	1
1	4091 08	2	1
1	4091 09	3	1
1	4091 11	6	1
1	4091 12	10	1
1	4091 14	16	1
1	4091 15	20	1
1	4091 16	25	1
1	4091 17	32	1
1	4091 18	40	1
1	4091 19	50	1
1	4091 20	63	1
1	4091 40	80	1
<b>Double pole 230/400 V~</b>			
1	4091 95	1	2
1	4091 96	2	2
1	4091 97	3	2
1	4091 99	6	2
1	4092 00	10	2
1	4092 02	16	2
1	4092 03	20	2
1	4092 04	25	2
1	4092 05	32	2
1	4092 06	40	2
1	4092 07	50	2
1	4092 08	63	2
1	4092 28	80	3
1	4092 29	100	3
1	4092 30	125	3
<b>Triple pole 400 V~</b>			
1	4092 47	1	3
1	4092 48	2	3
1	4092 49	3	3
1	4092 51	6	3
1	4092 52	10	3
1	4092 54	16	3
1	4092 55	20	3
1	4092 56	25	3
1	4092 57	32	3
1	4092 58	40	3
1	4092 59	50	3
1	4092 60	63	3
1	4092 80	80	4-5
1	4092 81	100	4-5
1	4092 82	125	4-5
<b>Four pole 400 V~</b>			
1	4093 29	1	4
1	4093 30	2	4
1	4093 31	3	4
1	4093 33	6	4
1	4093 34	10	4
1	4093 36	16	4
1	4093 37	20	4
1	4093 38	25	4
1	4093 39	32	4
1	4093 40	40	4
1	4093 41	50	4
1	4093 42	63	4
1	4093 62	80	6
1	4093 63	100	6
1	4093 64	125	6

## MCBs DX<sup>3</sup> 10000 - 16 kA **NEW**

thermal magnetic circuit breakers from 1 A to 125 A (continued)



4095 08

Dimensions **p. 65**  
 Technical information **p. 59-60**

Conform to IEC 60898-1

Breaking capacity

10000 - IEC 60898-1 - 400 V~

16 kA - IEC 60947-2 - 400 V~

Can be equipped with DX<sup>3</sup> auxiliaries and accessories **p. 58**

Pack	Cat. Nos.	MCBs DX <sup>3</sup> 10000 - 16 kA - D curve	
<b>Single pole 230/400 V~</b>			
	D curve	Nominal rating I <sub>n</sub> (A)	Number of modules
1	4094 25	2	1
1	4094 28	6	1
1	4094 30	10	1
1	4094 32	16	1
1	4094 33	20	1
1	4094 34	25	1
1	4094 35	32	1
1	4094 36	40	1
1	4094 37	50	1
1	4094 38	63	1
<b>Double pole 230/400 V~</b>			
1	4094 44	2	2
1	4094 47	6	2
1	4094 49	10	2
1	4094 51	16	2
1	4094 52	20	2
1	4094 53	25	2
1	4094 54	32	2
1	4094 55	40	2
1	4094 56	50	2
1	4094 57	63	2
1	4094 58	80	3
1	4094 59	100	3
1	4094 60	125	3
<b>Triple pole 400 V~</b>			
1	4094 92	2	3
1	4094 95	6	3
1	4094 97	10	3
1	4094 99	16	3
1	4095 00	20	3
1	4095 01	25	3
1	4095 02	32	3
1	4095 03	40	3
1	4095 04	50	3
1	4095 05	63	3
1	4095 06	80	4.5
1	4095 07	100	4.5
1	4095 08	125	4.5
<b>Four pole 400 V~</b>			
1	4095 26	2	4
1	4095 29	6	4
1	4095 31	10	4
1	4095 33	16	4
1	4095 34	20	4
1	4095 35	25	4
1	4095 36	32	4
1	4095 37	40	4
1	4095 38	50	4
1	4095 39	63	4
1	4095 40	80	6
1	4095 41	100	6
1	4095 42	125	6

## MCBs DX<sup>3</sup> 6000 - 10 kA **NEW**

thermal magnetic circuit breakers from 1 A to 63 A



4079 65



4080 25

Dimensions **p. 65**  
 Technical information **p. 59**

Conform to IEC 60898-1

Breaking capacity

6000 - IEC 60898-1 - 400 V~

10 kA - IEC 60947-2 - 400 V~

Can be equipped with DX<sup>3</sup> auxiliaries and accessories **p. 58**

Pack	Cat. Nos.	MCBs DX <sup>3</sup> 6000 - 10 kA - D curve	
<b>Single pole 230/400 V~</b>			
	D curve	Nominal rating I <sub>n</sub> (A)	Number of modules
1	4079 63	1	1
1	4079 65	3	1
1	4079 66	4	1
<b>Double pole 230/400 V~</b>			
1	4080 23	1	2
1	4080 25	3	2
1	4080 26	4	2
<b>Triple pole 400 V~</b>			
1	4080 81	1	3
1	4080 83	3	3
1	4080 84	4	3

Auxiliaries and accessories **p. 58**



Download the full file at

<http://assets.kempstoncontrols.com/doc/Legrand%20Industrial%20and%20power%20protection%20catalogue.pdf>



**KEMPSTON**  
CONTROLS