

SITOR cylindrical fuse link, 22 x 58 mm, 80 A, aR, Un AC: 690 V, Un DC: 700 V, DC acc. to UL



Figure similar

Model	
Product designation	SITOR cylindrical fuse link
Design of the product	DC acc. to UL
General technical data	
Operating class of the fuse link	aR
Size of the fuse link	22x58 mm
Supply voltage / at DC	700 V
Dissipation	
Power loss [W]	13.5 W
Power loss [W]	13.5 W
<ul style="list-style-type: none"> • for rated value of the current / at AC / in hot operating state / per pole 	
Main circuit	
Operating voltage / rated value	690 V
Operating current / Rated value	80 A
Product details	

Product component / striker	No
Mounting position	Any, preferably vertical
Net weight	56 g
<ul style="list-style-type: none"> Reference identifier / acc. to DIN EN 61346-2 	F
<ul style="list-style-type: none"> Reference identifier / acc. to DIN EN 81346-2 	F

General Product Approval	Declaration of Conformity
---------------------------------	----------------------------------



[Miscellaneous](#)



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NC2280>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NC2280>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NC2280

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

