

circuit breaker VL250N standard breaking capacity  $I_{cu}=55kA$ , 415V AC 4-pole, non-auto. air circ. br. Electronic Trip Unit magnetic  $I_n=250A$ , rated current  $I_l=3500A$ , short-circuit protection without auxiliary release without auxiliary/alarm switch

Model	
type of the driving mechanism motor drive	No
design of the overcurrent release	M
General technical data	
number of poles	4
size of the circuit-breaker	3VL3
mechanical service life (operating cycles) typical	20 000
electrical endurance (operating cycles) typical	10 000
utilization category	A
performance class for circuit breaker	N
reference code according to DIN 40719 extended according to IEC 204-2 according to IEC 750	Q
operating frequency maximum	120 1/s
Voltage	
Rated operational voltage $U_e$ max.	690 V
<ul style="list-style-type: none"> <li>insulation voltage rated value</li> <li>insulation voltage (<math>U_i</math>) at AC rated value</li> </ul>	800 V
surge voltage resistance rated value	8 kV
operating voltage	
<ul style="list-style-type: none"> <li>rated value maximum</li> <li>for main current circuit at AC at 50 Hz maximum</li> <li>for main current circuit at AC at 60 Hz maximum</li> <li>for main current circuit at DC maximum</li> </ul>	690 V 690 V 690 V 500 V
Protection class	
protection class IP	IP20
protection function of the overcurrent release	I
Current	
operational current	
<ul style="list-style-type: none"> <li>at 40 °C rated value</li> <li>at 45 °C rated value</li> <li>at 50 °C rated value</li> <li>at 55 °C rated value</li> <li>at 60 °C rated value</li> <li>at 65 °C rated value</li> <li>at 70 °C rated value</li> </ul>	250 A 250 A 250 A 232.5 A 232.5 A 215 A 215 A
continuous current rated value	250 A
derating temperature for the rated value of the continuous current	50 °C
adjustable current response value current	
<ul style="list-style-type: none"> <li>of instantaneous short-circuit trip unit minimum</li> <li>of instantaneous short-circuit trip unit maximum</li> </ul>	3 500 A 3 500 A
Main circuit	
operating frequency	
<ul style="list-style-type: none"> <li>1 rated value</li> <li>2 rated value</li> </ul>	50 Hz 60 Hz
Auxiliary circuit	
number of CO contacts for auxiliary contacts	0
number of NC contacts for auxiliary contacts	0
number of NO contacts for auxiliary contacts	0
Suitability	

suitability for use		non-automatic circuit-breakers	
<b>Product details</b>			
product component			
<ul style="list-style-type: none"> <li>• trip indicator</li> <li>• auxiliary switch</li> <li>• voltage trigger</li> <li>• undervoltage release</li> <li>• undervoltage release with leading contact</li> </ul>		No	No
product extension optional motor drive		No	Yes
<b>Product function</b>			
product function			
<ul style="list-style-type: none"> <li>• of thermal overload trip unit</li> <li>• grounding protection</li> <li>• for neutral conductors short-circuit and overload proof</li> <li>• overload protection</li> </ul>		without	No
		No	No
		No	No
<b>Short circuit</b>			
operating short-circuit current breaking capacity (Ics)			
<ul style="list-style-type: none"> <li>• at 240 V rated value</li> <li>• at 415 V rated value</li> <li>• at 500 V rated value</li> <li>• at 690 V rated value</li> </ul>		65 kA	55 kA
		20 kA	6 kA
maximum short-circuit current breaking capacity (Icu)			
<ul style="list-style-type: none"> <li>• at 240 V rated value</li> <li>• at 415 V rated value</li> <li>• at 440 V rated value</li> <li>• at 480 V according to NEMA rated value</li> <li>• at 500 V rated value</li> <li>• at 600 V according to NEMA rated value</li> <li>• at 690 V rated value</li> </ul>		65 kA	55 kA
		25 kA	25 kA
		25 kA	12 kA
		12 kA	12 kA
<b>Connections</b>			
arrangement of electrical connectors for main current circuit		front side	
type of connectable conductor cross-sections for main contacts			
<ul style="list-style-type: none"> <li>• with flexible busbar</li> <li>• solid</li> <li>• finely stranded with core end processing</li> <li>• stranded</li> </ul>		17 x 10 mm	25 ... 185 mm <sup>2</sup>
		25 ... 120 mm <sup>2</sup>	25 ... 185 mm <sup>2</sup>
type of connectable conductor cross-sections for auxiliary contacts			
<ul style="list-style-type: none"> <li>• solid</li> <li>• finely stranded with core end processing</li> </ul>		0.75 ... 1.5 mm <sup>2</sup>	0,75 ... 1.0 mm <sup>2</sup>
type of electrical connection for main current circuit		screw-type terminals	
<b>Mechanical Design</b>			
height		185.5 mm	
width		139.5 mm	
depth		106.5 mm	
fastening method		fixed mounting	
<b>Environmental conditions</b>			
ambient temperature during operation			
<ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>		0 °C	70 °C
ambient temperature during storage			
<ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>		-40 °C	80 °C
<b>General Product Approval</b>			

[Miscellaneous](#)



[Confirmation](#)

[TSE](#)

[KC](#)



EMC	Declaration of Conformity	Test Certificates	Marine / Shipping
-----	---------------------------	-------------------	-------------------



[Special Test Certificate](#)



Marine / Shipping	other
-------------------	-------



[Confirmation](#)

other
-------

[Environmental Confirmations](#)

[Miscellaneous](#)

[Miscellaneous](#)

Further information
---------------------

**Information on the packaging**

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mifb=3VL3725-1EE46-0AA0>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3VL3725-1EE46-0AA0>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mifb=3VL3725-1EE46-0AA0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mifb=3VL3725-1EE46-0AA0)

**CAx-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>



