

## Main/Emergency-Off Switches

- Front mounting switches with single hole mounting
- 3 up to 8 pole
- 20 A up to 63 A
- IP66



Switching programme	Rated data (IEC 60947)			Mounting dimension  (mm)	Padlock device N-handle yellow/red	Padlock device M-handle yellow/red	Padlockable handle V-handle yellow/red
	Operat. current $I_e$	Operational power (at 380–440 V)			 IP66	 IP66	 IP66
	AC-21A (A)	AC-23A (kW)	AC-3 (kW)		Order code number	Order code number	Order code number
<b>41300</b> – 3 pole – without auxiliary contacts  	20	5.5	3.7	∅ 22.5	H216-41300-206N4	H216-41300-206M4	H216-41300-206V4
	20	5.5	3.7	∅ 30.5	H216-41300-216N4	H216-41300-216M4	H216-41300-216V4
	25	7.5	5.5	∅ 22.5	H220-41300-206N4	H220-41300-206M4	H220-41300-206V4
	25	7.5	5.5	∅ 30.5	H220-41300-216N4	H220-41300-216M4	H220-41300-216V4
	32	11	7.5	∅ 22.5	H226-41300-206N4	H226-41300-206M4	H226-41300-206V4
	32	11	7.5	∅ 30.5	H226-41300-216N4	H226-41300-216M4	H226-41300-216V4
	40	15	11	∅ 22.5	H233-41300-206N4	H233-41300-206M4	H233-41300-206V4
	40	15	11	∅ 22.5	B240-41300-206N4*	B240-41300-206M4*	B240-41300-206V4*
	40	15	11	∅ 30.5	H233-41300-216N4	H233-41300-216M4	H233-41300-216V4
	40	15	11	∅ 30.5	B240-41300-216N4*	B240-41300-216M4*	B240-41300-216V4*
	50	18.5	15	∅ 22.5	B250-41300-206N4	B250-41300-206M4	B250-41300-206V4
	50	18.5	15	∅ 30.5	B250-41300-216N4	B250-41300-216M4	B250-41300-216V4
	63	22	18.5	∅ 22.5	B263-41300-206N4	B263-41300-206M4	B263-41300-206V4
	63	22	18.5	∅ 30.5	B263-41300-216N4	B263-41300-216M4	B263-41300-216V4
<b>41400</b> – 4 pole – without auxiliary contacts – neutral contact early make/late break  	20	5.5	3.7	∅ 22.5	H216-41400-206N4	H216-41400-206M4	H216-41400-206V4
	20	5.5	3.7	∅ 30.5	H216-41400-216N4	H216-41400-216M4	H216-41400-216V4
	25	7.5	5.5	∅ 22.5	H220-41400-206N4	H220-41400-206M4	H220-41400-206V4
	25	7.5	5.5	∅ 30.5	H220-41400-216N4	H220-41400-216M4	H220-41400-216V4
	32	11	7.5	∅ 22.5	H226-41400-206N4	H226-41400-206M4	H226-41400-206V4
	32	11	7.5	∅ 30.5	H226-41400-216N4	H226-41400-216M4	H226-41400-216V4
	40	15	11	∅ 22.5	H233-41400-206N4	H233-41400-206M4	H233-41400-206V4
	40	15	11	∅ 22.5	B240-41400-206N4*	B240-41400-206M4*	B240-41400-206V4*
	40	15	11	∅ 30.5	H233-41400-216N4	H233-41400-216M4	H233-41400-216V4
	40	15	11	∅ 30.5	B240-41400-216N4*	B240-41400-216M4*	B240-41400-216V4*
	50	18.5	15	∅ 22.5	B250-41400-206N4	B250-41400-206M4	B250-41400-206V4
	50	18.5	15	∅ 30.5	B250-41400-216N4	B250-41400-216M4	B250-41400-216V4
	63	22	18.5	∅ 22.5	B263-41400-206N4	B263-41400-206M4	B263-41400-206V4
	63	22	18.5	∅ 30.5	B263-41400-216N4	B263-41400-216M4	B263-41400-216V4

\* larger terminal capacity, see page 154

Further switching programmes from page 132.