



8330 00



8332 02



8334 03



8331 51



8333 57

Slim front plate:

BSS: Plates made of austenitic Stainless Steel - non-magnetic - grade 304 L

PSS: Plates made of Stainless Steel + rust resistance

G: Plates made of Stainless Steel + rust resistance

Terminal screws captive and backed off ready for cabling - large angled terminal entries. Compact mechanism for maximum wiring space

### Pack Cat.Nos. Single pole plate switches 10 AX - 250 V~

Conform to BS EN 60669-1  
Flush mounting back box : min. 16 mm deep

#### 1 gang - 1 way switch

Nominal plate dimensions : 86 x 86 mm

- |   |         |  |                            |
|---|---------|--|----------------------------|
| 1 | 8330 00 |  | ● Brushed stainless steel  |
| 1 | 8332 00 |  | ● Polished stainless steel |
| 1 | 8334 00 |  | ● Gold                     |

#### 1 gang - 2 way switch

Nominal plate dimensions : 86 x 86 mm

- |   |         |  |                            |
|---|---------|--|----------------------------|
| 1 | 8330 01 |  | ● Brushed stainless steel  |
| 1 | 8332 01 |  | ● Polished stainless steel |
| 1 | 8334 01 |  | ● Gold                     |

#### 1 gang - intermediate switch

Nominal plate dimensions : 86 x 86 mm

- |   |         |  |                            |
|---|---------|--|----------------------------|
| 1 | 8330 05 |  | ● Brushed stainless steel  |
| 1 | 8332 05 |  | ● Polished stainless steel |
| 1 | 8334 05 |  | ● Gold                     |

#### 2 gang - 2 way switch

Nominal plate dimensions : 86 x 86 mm

- |   |         |  |                            |
|---|---------|--|----------------------------|
| 1 | 8330 02 |  | ● Brushed stainless steel  |
| 1 | 8332 02 |  | ● Polished stainless steel |
| 1 | 8334 02 |  | ● Gold                     |

#### 3 gang - 2 way switch

Nominal plate dimensions : 86 x 86 mm

- |   |         |  |                            |
|---|---------|--|----------------------------|
| 1 | 8330 03 |  | ● Brushed stainless steel  |
| 1 | 8332 03 |  | ● Polished stainless steel |
| 1 | 8334 03 |  | ● Gold                     |

#### 4 gang - 2 way switch

Nominal plate dimensions : 86 x 146 mm

- |   |         |  |                            |
|---|---------|--|----------------------------|
| 1 | 8330 04 |  | ● Brushed stainless steel  |
| 1 | 8332 04 |  | ● Polished stainless steel |
| 1 | 8334 04 |  | ● Gold                     |

### Single pole push switches 10 A - 250 V~

Conform to BS EN 60669-1  
Flush mounting back box : min. 16 mm deep  
Nominal plate dimensions : 86 x 86 mm

#### 1 gang - 2 way push switch

- |   |         |  |                            |
|---|---------|--|----------------------------|
| 1 | 8330 07 |  | ● Brushed stainless steel  |
| 1 | 8332 07 |  | ● Polished stainless steel |
| 1 | 8334 07 |  | ● Gold                     |

### Single pole plate switches 20 AX - 250 V~

Conform to BS EN 60669-1  
Flush mounting back box : min. 16 mm deep  
Nominal plate dimensions : 86 x 86 mm

#### 1 gang - 2 way switch

- |   |         |  |                            |
|---|---------|--|----------------------------|
| 1 | 8331 31 |  | ● Brushed stainless steel  |
| 1 | 8333 31 |  | ● Polished stainless steel |
| 1 | 8335 31 |  | ● Gold                     |

### Pack Cat.Nos. Single pole plate switches 20 AX - 250 V~

Conform to BS EN 60669-1  
Flush mounting back box : min. 16 mm deep  
Nominal plate dimensions : 86 x 86 mm

#### 2 gang - 2 way switch

- |   |         |  |                            |
|---|---------|--|----------------------------|
| 1 | 8331 32 |  | ● Brushed stainless steel  |
| 1 | 8333 32 |  | ● Polished stainless steel |
| 1 | 8335 32 |  | ● Gold                     |

#### 3 gang - 2 way switch

- |   |         |  |                            |
|---|---------|--|----------------------------|
| 1 | 8331 33 |  | ● Brushed stainless steel  |
| 1 | 8333 33 |  | ● Polished stainless steel |
| 1 | 8335 33 |  | ● Gold                     |

### Push on/off rotary universal dimmer 5 W/300 W

Conform to IEC 60669-2-1  
Flush mounting back box : min. 40 mm deep  
Equipped with overvoltage and short-circuit protection  
Screw terminals. For all types of lamps :  
- dimmable LEDs : 5 W to 75 W  
- dimmable compact fluorescent lamps : 5 W to 75 W  
- halogen with ferromagnetic or electronic transformer : 5 VA to 300 VA  
- fluorescent tube - ballast : 5 VA to 300 VA  
- halogen and incandescent 230 V : 5 W to 300 W  
When switched on, gradually (2 seconds) lights up at the level set before last switch-off  
Nominal plate dimensions : 86 x 86 mm

#### 1 gang - 2 way push switch

- |   |         |  |                            |
|---|---------|--|----------------------------|
| 1 | 8331 51 |  | ● Brushed stainless steel  |
| 1 | 8333 51 |  | ● Polished stainless steel |
| 1 | 8335 51 |  | ● Gold                     |

### Push on/off rotary dimmer 400 W 100-240 V~ - 50/60 Hz

Conform to BS EN 60669-1-2  
Flush mounting back box : min. 25 mm deep  
Nominal plate dimensions : 86 x 86 mm

#### 1 gang - 2 way

- |   |         |  |                            |
|---|---------|--|----------------------------|
| 1 | 8331 56 |  | ● Brushed stainless steel  |
| 1 | 8333 56 |  | ● Polished stainless steel |
| 1 | 8335 56 |  | ● Gold                     |

#### 2 gang - 2 way

- |   |         |  |                            |
|---|---------|--|----------------------------|
| 1 | 8331 57 |  | ● Brushed stainless steel  |
| 1 | 8333 57 |  | ● Polished stainless steel |
| 1 | 8335 57 |  | ● Gold                     |

### Push on/off rotary dimmer 1000 W 100-240 V/50-60 Hz

Conform to BS EN 60669-1  
- Flush mounting back box : min. 40 mm deep  
- 60-1000 W (230 V)  
- 60-500 W (127 V) for incandescent and halogen lamps  
60-600 VA (230 V)  
- 60-300 VA (127 V) for halogen lamps with electronic transformers  
60-100 VA (230 V)  
- 60-500 VA (127 V) for halogen lamps with ferromagnetic transformers  
Nominal plate dimensions : 86 x 86 mm

#### 1 gang

- |   |         |  |                            |
|---|---------|--|----------------------------|
| 1 | 8331 50 |  | ● Brushed stainless steel  |
| 1 | 8333 50 |  | ● Polished stainless steel |
| 1 | 8335 50 |  | ● Gold                     |

# Synergy® Authentic

British standard socket outlets



8330 65



8332 75



8330 60



8334 61



8332 71

Slim front plate:

BSS: Plates made of austenitic Stainless Steel - non-magnetic - grade 304 L

PSS: Plates made of Stainless Steel + rust resistance

G: Plates made of Stainless Steel + rust resistance

Terminal screws captive and backed off ready for cabling - large angled terminal entries

Compact mechanism for maximum wiring space

Pack	Cat.Nos.	Socket outlets 13 A - 250 V~
		Conform to BS 1363 : Part. 2 With safety shutter mechanism Flush mounting back box : min. 25 mm deep ASTA licence
		<b>1 gang unswitched</b> Nominal plate dimensions : 86 x 86 mm
1	8330 65	● Brushed stainless steel
1	8332 65	● Polished stainless steel
1	8334 65	● Gold
		<b>2 gang unswitched</b> Nominal plate dimensions : 86 x 146 mm
1	8330 75	● Brushed stainless steel
1	8332 75	● Polished stainless steel
1	8334 75	● Gold

Pack	Cat.Nos.	Double pole socket outlets 13 A - 250 V~
		Conform to BS 1363 : Part. 2 With safety shutter mechanism Flush mounting back box : min. 25 mm deep ASTA licence
		<b>1 gang switched</b> Nominal plate dimensions : 86 x 86 mm
1	8330 60	● Brushed stainless steel
1	8332 60	● Polished stainless steel
1	8334 60	● Gold
		<b>1 gang switched with blue LED power indicator</b> Nominal plate dimensions : 86 x 86 mm
1	8330 61	● Brushed stainless steel
1	8332 61	● Polished stainless steel
1	8334 61	● Gold
		<b>2 gang switched</b> Nominal plate dimensions : 86 x 146 mm
1	8330 70	● Brushed stainless steel
1	8332 70	● Polished stainless steel
1	8334 70	● Gold
		<b>2 gang switched with blue LED power indicator</b> Nominal plate dimensions : 86 x 146 mm
1	8330 71	● Brushed stainless steel
1	8332 71	● Polished stainless steel
1	8334 71	● Gold
		<b>2 gang switched outboard for standard and clean earth applications</b> Nominal plate dimensions : 86 x 146 mm
1	8330 74	● Brushed stainless steel
1	8332 74	● Polished stainless steel
1	8334 74	● Gold

Pack	Cat.Nos.	Key switched socket outlets 13 A - 250 V~
		Conform to BS 1363 - Part. 2 : 1995 Flush mounting back box : min. 35 mm deep Nominal plate dimensions : 86 x 146 mm
1	8216 57	● Brushed stainless steel
1	8216 58	● Polished stainless steel
1	8216 59	● Gold

Download the full file at

<http://assets.kempstoncontrols.com/doc/Synergy%20Wiring%20Accessories.pdf>



**KEMPSTON**  
CONTROLS