


PRODUCT-DETAILS

M4/8.D2.SF

M4/8.D2.SF Screw Clamp Terminal Blocks - For 5 x 20 and 5 x 25 fuses - Grey



General Information

Extended Product Type	M4/8.D2.SF
Product ID	1SNA115604R2100
EAN	3472591156041
Catalog Description	M4/8.D2.SF Screw Clamp Terminal Blocks - For 5 x 20 and 5 x 25 fuses - Grey
Long Description	- Protect your circuits with 5x20 and 5x25 fuse terminal blocks (fuse not supplied with terminal blocks), - Save space with double deck terminal blocks: 2 independent circuits 1 fuse on upper deck + 1 feed-through.

Ordering

Color	Grey
Minimum Order Quantity	50 piece
Customs Tariff Number	85361010

Popular Downloads

Data Sheet, Technical Information	1SNC160019C0202
Instructions and Manuals	1SNC160019C0202

Dimensions

Product Net Width	8 mm
-------------------	------

Product Net Height	85.7 mm
Product Net Depth / Length	59 mm
Product Net Weight	26 g

Technical

Rated Cross-Section	4 mm ²
Spacing	8 mm
Connection Type	Screw Clamp
Function	Fuse
Number of Levels	2
Connecting Capacity Main Circuit	Screw Clamp / Flexible 1x 0.5 ... 4 mm ² Screw Clamp / Rigid 1x 0.5 ... 6 mm ²
Gauge Type	A4
Rated Current (I _n)	Main Circuit 6.3 A
Rated Voltage (U _r)	630 V
Rated Impulse Withstand Voltage (U _{imp})	8000 V
Pollution Degree	3
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Insulation Material	Polyamide
Mounting on DIN Rail	G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Wire Stripping Length	9.5 mm
Recommended Screw Driver	4 mm
Tightening Torque	acc. IEC 60947-1 0.5 N·m Manufacturer 0.8 N·m

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 300 V
Connecting Capacity Main Circuit UL/CSA	Screw Clamp / Rigid 1x 24 ... 12 AWG
Connecting Capacity UL/CSA	Screw Clamp / Rigid 24 ... 12 AWG Stranded 12 AWG
Flammability According to UL94	V-0

Environmental

Ambient Air Temperature	Operation -55 ... +110 °C Storage -55 ... +110 °C
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Certificates and Declarations (Document Number)

CSA Certificate	1SND161066A0201
cUL Certificate	1SND161002A0202
Declaration of Conformity - CE	1SND225016U1000
EAC Certificate	1SND161009A1100
Environmental Information	1SND220021E1002
Instructions and	1SNC160019C0202

Manuals

RoHS Information

1SND230023F0208

Classifications

Object Classification Code	X
ETIM 4	EC000899 - Fuse terminal block
ETIM 5	EC000899 - Fuse terminal block
ETIM 6	EC000899 - Fuse terminal block

Container Information

Package Level 1 Units	50 piece
Package Level 1 Width	176 mm
Package Level 1 Depth / Length	200 mm
Package Level 1 Height	75 mm
Package Level 1 Gross Weight	1.3 kg
Package Level 1 EAN	3472591156041
Package Level 2 Units	450 piece
Package Level 2 Width	300 mm
Package Level 2 Depth / Length	500 mm
Package Level 2 Height	300 mm
Package Level 2 Gross Weight	11.7 kg
Package Level 3 Units	10800 piece

Categories

Low Voltage Products and Systems → Connection Devices → Terminal Blocks → SNA Series

