

RVD3 RVA3



MODELS

Features:

- 75 amp total rating allows 25 amps per phase for three phase load
- 500 volt
- Internal MOV
- Superior Surge Survival™
- DC logic and AC logic inputs available
- fuses are external using triple fuseholder and fuses
- CE compliant
- UL recognised
- CSA certified

Three phase solid state relay with integral heatsink

Ratings

The current rating of the RVD3 and RVA3 is 75 amps total current. This means that for three phase application, the limit is 25 amps per phase. Voltage rating is 500 volts, AC.

Superior Surge Survival™ is a technique used to provide greater immunity to voltage transients. Internal MOVs provide additional protection.

Inputs

The RVD3 accepts a DC Logic signal and the RVA3 an AC Logic signal.

Firing mode

All units are Logic firing with zero voltage switching.

Fusing

External high speed fuses are available, mounted in a triple fuseholder.

Cooling

The built in heat sink is cooled by natural convection.

SPECIFICATIONS

Electrical ratings	
Current	25amp per phase (max) for 3 pole, 35 amps per phase 2 pole 40 amps for single phase
Voltage range	500Vac (24V-560V)
Frequency	47-63Hz
Blocking voltage	1400 volts
Isolation	4000V
DC input	
Turn on voltage	4V(min) 32V(max) 8mA max
Turn off voltage	1 volt (max)
Reverse voltage protection	-100V
AC input	
Turn on voltage	100V (min) 280V(max) 25mA max
Turn off voltage	20 volts (max)
Voltage drop	3V
Holding current	100mA
Residual current	8mA max
Indication	LED input status indication
Firing mode	Logic (on/off) with zero voltage switching
Dimensions (mm)	87(H) x 90(W) x 98(D)
Fuseholder dimensions (mm)	95(H) x 79(W) x 86(D)
Environment	
Operating temperature	0 to 40°C
Humidity	5% to 95% non condensing, non streaming
Atmosphere	Non corrosive, non explosive, and non conducting
Altitude	2000 metres maximum
Pollution	Pollution degrade 2 admissible, defined by IEC644

ORDERING CODE

DC Logic input

RVD3/5V75T/L/A2

AC Logic input

RVA3/5V75T/H/A2

FUSES

Fuse and fuseholder (triple)

CFU351/32A/00

Spare fuses

3 off CH330044

EUROTHERM LIMITED UK

Faraday Close Durrington Worthing BN13 3PL United Kingdom

Tel. +44 (0)1903 205277 Fax +44 (0)1903 236465

Email info@eurotherm.co.uk

Web www.eurotherm.co.uk

EUROTHERM US

741-F Miller Drive Leesburg VA 20175-8993

Tel. 1-703-443-0000 Fax 1-703-669-1300

Email info@eurotherm.com

Web www.eurotherm.com

© Copyright Eurotherm Limited 2003

All rights are strictly reserved. No part of this document may be reproduced, modified, or transmitted in any form by any means, nor may it be stored in a retrieval system other than for the purpose to act as an aid in operating the equipment to which the document relates, without the prior written permission of Eurotherm limited.

Eurotherm Limited pursues a policy of continuous development and product improvement. The specifications in this document may therefore be changed without notice. The information in this document is given in good faith, but is intended for guidance only. Eurotherm Limited will accept no responsibility for any losses arising from errors in this document.

