


PNOZ 1 110-120VAC 3n/o 1n/c

775630



Safety relay (standalone) Inputs: 1-/2-channel wiring without detection of shorts across contacts Outputs: 3 N/O, 1 N/C UB 110-120 V AC, width: 90 mm, plug-in terminals of screw type Monitoring E-STOP, safety gates.

Technical details

Approvals:	CE;cULus Listed;EAC (Eurasian);TÜV;CCC
Application options:	Safety gate monitor;Instantaneous E-STOP monitoring;Limit switch
Operating modes:	Single-channel;Automatic reset;Dual-channel;Manual reset
Product standard:	EN 60947-5-1
Standards:	EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1
Supply voltage (V):	110,0 - 120,0
Supply voltage type:	AC
Terminal style:	fixed
Terminal type:	Screw terminal
Number of instantaneous safety contacts:	3
Number of auxiliary contacts:	1
Stop category:	0
Max. current at DC13 I (6 cycles/min):	7.0 A
Max. current at AC15:	5.0 A
Width dimension:	90.0 mm
Height dimension:	87.0 mm
Depth dimension:	121.0 mm
Gross weight:	510 g
Net weight:	500 g
Ambient temperature:	-10 - 55 °C