

1) Optical axis receiver 2) Optical axis emitter 3) Operating voltage 4) Light reception/limit area 5) Sn



Display/Operation

Adjuster	Potentiometer 270°
Display	LED green: Power Limit range - LED yellow, flashing LED yellow: Light received
Setting	Rated switching distance (Sn)

EN 60068-2-27, Shock
 EN 60068-2-6, Vibration

Half-sinus, 30 gn, 11 ms, 3x6
 10...55 Hz, amplitude 1 mm,
 3x30 min
 IP67

Functional safety

MTTF (40 °C)	1428 a
--------------	--------

Electrical connection

Connection	Connector, M12x1-Male, 4-pole
Contact, surface protection	Gold plated
Polarity reversal protected	yes
Protection against device mix-ups	yes
Short-circuit protection	yes

General data

Approval/Conformity	CE cULus EAC WEEE
Basic standard	IEC 60947-5-2
Principle of operation	Photoelectric sensor
Series	12M
Style	Cylinder Straight optics

Electrical data

Load capacitance max. at Ue	0.2 µF
Operating voltage Ub	10...30 VDC
Rated insulation voltage Ui	75 V DC
Rated operating current Ie	100 mA
Rated operating voltage Ue DC	24 V
Ripple max. (% of Ue)	15 %
Switching frequency	1000 Hz
Turn-off delay toff max.	0.5 ms
Turn-on delay ton max.	0.5 ms
Utilization category	DC -13
Voltage drop Ud max. at Ie	1.5 V

Material

Housing material	Brass
Material sensing surface	PMMA
Surface protection	nickel plated

Mechanical data

Dimension	Ø 12 x 60 mm
Mounting	Nut M12x1
Tightening torque max.	7 Nm 15 Nm

Environmental conditions

Ambient temperature	-5...55 °C
Contamination scale	3

Optical data

Ambient light max.	10000 Lux
Beam characteristic	Divergent
LED group per IEC 62471	Exempt Group
Light spot size	45 x 45 mm at 400 mm
Light type	LED infrared
Principle of optical operation	Diffuse sensor, energetic
Switching function, optical	Light-on
Wave length	850 nm

Output/Interface

Switching output	PNP normally open (NO) Pin 4
------------------	------------------------------

Range/Distance

Hysteresis H max. (% of Sr)	10.0 %
Range	1...400 mm
Rated operating distance Sn	400 mm Adjustable
Temperature drift max. (% of Sr)	10 %

Remarks


Order accessories separately.
For additional information, refer to user's guide.
Reference object (target): gray card, 200 x 200, 90 % remission, axial approach.
The sensor is functional again after the overload has been eliminated.
For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Connector view



Wiring Diagram



Symbols for Optoelectronic Sensors

