

HDA080U

Moulded Case Circuit Breaker h3 x160 TM ADJ 3P3D 80A 18kA CTC



- Architecture
 - Neutral position without neutral
 - Number of poles 3 P
 - Type of pole 3P3D
 - Fixing mode DIN rail type O or type J
- Main electrical features
 - Rated operational voltage Ue 220 / 415 V
 - Frequency 50;60 Hz
 - Rated current 80 A
- Voltage
 - Rated insulation voltage 690 V
 - Rated impulse withstand voltage 8000 V
- Electric current
 - Rated service breaking capacity Ics under 400V AC according IEC 60947-2 18 kA
- Electric current / temperature
 - Rating current 30°C according to IEC 60947-2 86.8 A

- Dimensions
 - Depth of installed product
68 mm
 - Height of installed product
130 mm
 - Width of installed product
75 mm
- Power
 - Total power loss under IN
32.1 W
- Tripping
 - Short-time delayed tripping
No
- Endurance
 - Electric endurance in number of cycles
1000
 - Number of mechanical operations
4000
- Cover, door
 - Interlockable
No
- Connection
 - Type of connection
with screw
- Equipment
 - Number of auxiliary contacts as normally closed contact
0
 - Number of auxiliary contacts as normally open contact
0
 - Number of auxiliary contacts as change-over contact
0
 - Can be accessorized
Yes
- Standards
 - Standard text
IEC 60947-2
 - European directive WEEE
concerned
- Safety
 - Protection index IP
IP4X