

equipment for Atlantic metal cabinets



Cabinet and equipment selection chart **p. 262-263**
Technical characteristics **p. 266**

Pack	Cat.Nos	Cabstop open-work plate IP 55
		<p>Cable entries consisting of a cable clamp providing the mechanical grip, and elastomer areas for weatherproofing</p> <p>Can be pierced using the cable (no tool required)</p> <p>Fits the cable perfectly</p> <p>Replacement of a cable possible</p> <p>Fire retardant polypropylene RAL 7035</p> <p>2 possibilities of mounting:</p> <ul style="list-style-type: none"> - direct on cable entry of Atlantic, Atlantic-E or Marina cabinets - on flat surface with kit Cat.No 0 364 98 <p>Supplied with:</p> <ul style="list-style-type: none"> - locking caps for sealing a pierced entry providing IP 55 protection - cable release tool
1	0 364 94	Number of entries Ø5 to 14: 13
1	0 364 95	Number of entries Ø14 to 24: 1
1	0 364 96	Number of spare entries: 1
1	0 364 97	Direct mounting on cable entry of cabinet width (mm): 500-1000
1	0 364 98	600-800-1200
		<p>Kit for mounting Cabstop plate on plain plate</p> <p>Enables mounting of 2 Cabstop plates:</p> <p>Cat.Nos 0 364 94 or 95 and 0 364 96 or 97</p> <p>IP 55 maintained</p>
		Cable entries for Atlantic cabinets 600 or 800 mm width
1	0 329 46	IP 43 cable entry plate with brush (cable feed-through 385 x 30 mm)
1	0 329 47	IP 55 multi-entry cable entry plate with cable glands
		<p>Supplied with 12 ISO 32 cable glands</p> <p>The cable glands take 4 UTP/FTP/SFTP cables (Ø6.5 to 9.5 mm) per cable gland</p> <p>Cords with connectors can be fed through without having to dismantle the cable gland</p> <p>Usable interior Ø25.5 mm</p> <p>Supplied with blanking plates for unused entries</p>

Pack	Cat.Nos	Protective conductor
		Earth braid
20	0 347 95	Capacity (mm ²): 6
20	0 347 96	Fixing spacing (mm): 200
10	0 347 97	Ø of holes (mm): 8.5
		Green/yellow wire
20	0 363 95	Capacity (mm ²): 6
		Fixing spacing (mm): 200
		Ø of holes (mm): 6.5
		Paint touch-up
1	0 365 97	Aerosol paint spray
		RAL 7035
		Touch-up brush
		For protecting the sheet metal after cutting
10	0 365 91	Anti-corrosion paint
		RAL 7035
		Other colours on request
10	0 395 99	Temporary marking
		Water-soluble marker pen
		Accessories
1	0 367 45	Set of 4 slides for depth adjustment
		For 400 mm depth cabinets
1	0 364 01	Wall-mounting lugs (set of 4)
		For load up to 300 kg
		Horizontal or vertical installation
		With a roof, horizontal installation only
		Zamak RAL 7035
		Supplied with cover finish
1	0 364 04	Attachment lugs for rail
		For load up to 300 kg
		Horizontal or vertical installation
		Anti-corrosion steel treatment
5	0 367 35	Attachment lugs for rail
		Supplied with M6 screws
		Set of 2
		Used to attach the 15 mm depth symmetric rail on door profile strand-holder