

PMX420

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



Universal interfacing device, 4-character current/voltage displays and meter/totaliser with additional functions and external power supply.

The AMS400A interfacing devices are used between the control unit and field devices.

It carries out the manual simulation of automatically controlled loops. Typical applications are manual start-up of sensitive processes before handover to automatic control and manual override in case of controller failure or malfunction.

The current/voltage displays of the PMX420 series are available as a pure PMX420 display unit and optionally with analogue outputs or four alarm outputs

The basic model is suitable for displaying all standardised current or voltage signals.

The programmable meter components from the PTX800A are for measuring flow quantity: they process standardised analogue current and voltage signals. Linearisation and interference-suppression functions are available for processing measurement signals. In addition, the meters have a 24 VDC power supply for external loop-powered sensors.

General ordering data

Type	PMX420
Order No.	7940018956
Version	Signal converter/insulator, -22...+22 mA (preset to 4...20 mA)
GTIN (EAN)	4032248594214
Qty.	1 pc(s).

PMX420

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

Technical data

Dimensions and weights

Length	137 mm	Length (inches)	5.394 inch
Width	96.6 mm	Width (inches)	3.803 inch
Height	48.8 mm	Height (inches)	1.921 inch
Weight	353 g	Net weight	353 g

Temperatures

Humidity	0...90 % (no condensation)	Operating temperature	0 °C...60 °C
Ambient temperature	0 °C...+60 °C	Storage temperature	-25 °C...70 °C

Alarm

Switching current	5 A @ 240 V AC, 10 A @ 24 V DC	Type	not available
-------------------	-----------------------------------	------	---------------

Analogue output

Residual ripple (analogue output)	< 20 mV _{SS}
-----------------------------------	-----------------------

Display

Display range	-9999...9999	Display value	Percentage or real value display
Scaling	Variable	Type	4-digit, red LED, 14.2 mm

General data

Cut-off frequency (-3 dB)	5 Hz	Data backup	> 10 years without power supply
Humidity	0...90 % (no condensation)	Input/Output	Voltage/current input
Linearity	< 0.05 %	Long-term drift	0.1 % / 10.000 h
Power consumption	8.5 W @ 24 V DC	Supply voltage	18...50 V DC, other voltages on request
Switching current	5 A @ 240 V AC, 10 A @ 24 V DC	Transmit function	direct or inverted
Type of connection	Screw connection	Weight	353 g

Input

Attenuation factor	0...99, programmable digital filter	Input current	-22...+22 mA (preset to 4...20 mA)
Input resistance	25 Ω (current input) or 1.5 MΩ (voltage input)	Input voltage	-11...+11 V
Resolution	4 μA / 2 mV	Sensor current	4...20 mA
Type	Adjustable input for current or voltage		

Insulation coordination

EMC standards	DIN EN 61326	Impulse withstand voltage	4 kV (1.2/50 μs)
Standards	DIN EN 50178		

PMX420

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Output

Last resistor, max.	850 Ω @ 20 mA (current output) / < 500 Ω (voltage output)	Residual ripple (analogue output)	< 20 mV _{ss}
Scaling	Variable	Transmit function	direct or inverted
Type	not available		

Output current mode

Residual ripple (current mode output) < 1 μA

Connection data

Type of connection	Screw connection	Clamping range, rated connection	1.5 mm ²
Clamping range, rated connection, min.	0.5 mm ²	Clamping range, rated connection, max.	2.5 mm ²

Classifications

ETIM 3.0	EC001774	ETIM 4.0	EC001774
ETIM 5.0	EC001774	ETIM 6.0	EC000677
UNSPSC	30-21-18-01	eClass 6.2	27-21-09-90
eClass 7.1	27-21-09-90	eClass 8.1	27-21-09-90
eClass 9.0	27-21-09-90	eClass 9.1	27-21-03-01

Approvals

Approvals



ROHS Conform

Downloads

Approval/Certificate/Document of Conformity	Declaration of Conformity
Brochure/Catalogue	CAT 4.1 ELECTR 16/17 EN
User Documentation	Manual

Data sheet

PMX420

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

Electric symbol

