

circuit breaker VL160X N standard breaking capacity I<sub>cu</sub>=55kA, 415V AC 3-pole, line protection Trip Unit TM, LI I<sub>n</sub>=63A, rated current I<sub>r</sub>=63A, overload protection II=600A, short-circuit prot. without auxiliary release without auxiliary/alarm switch

Model	
type of the driving mechanism / motor drive	No
design of the overcurrent release	TM
General technical data	
number of poles	3
size of the circuit-breaker	3VL1
mechanical service life (switching cycles) / typical	20 000
electrical endurance (switching cycles) / typical	10 000
utilization category	A
performance class for circuit breaker	N
reference code / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750	Q
operating frequency / maximum	120 1/s
Voltage	
Rated operational voltage U <sub>e</sub> / max.	690 V
insulation voltage	
• rated value	800 V
• at AC / rated value	800 V
surge voltage resistance / rated value	8 kV
operating voltage	
• rated value / maximum	690 V
• for main current circuit / at AC / at 50 Hz / maximum	690 V
• for main current circuit / at AC / at 60 Hz / maximum	690 V
• for main current circuit / at DC / maximum	500 V
Protection class	
protection class IP	IP20
protection function of the overcurrent release	LI
Current	
operational current	
• at 40 °C / rated value	63 A
• at 45 °C / rated value	63 A
• at 50 °C / rated value	63 A
• at 55 °C / rated value	58.6 A
• at 60 °C / rated value	58.6 A
• at 65 °C / rated value	54.2 A
• at 70 °C / rated value	54.2 A
continuous current / rated value	63 A
derating temperature / for the rated value of the continuous current	50 °C
adjustable current response value current	
• of the current-dependent overload release / full-scale value	63 A
• of instantaneous short-circuit trip unit / minimum	600 A
• of instantaneous short-circuit trip unit / maximum	600 A
Main circuit	
operating frequency	
• 1 / rated value	50 Hz

• 2 / rated value	60 Hz
<b>Auxiliary circuit</b>	
number of CO contacts / for auxiliary contacts	0
number of NC contacts / for auxiliary contacts	0
number of NO contacts / for auxiliary contacts	0
<b>Suitability</b>	
suitability for use	system protection
<b>Adjustable parameters</b>	
adjustable current response value current / of the current-dependent overload release / initial value	63 A
<b>Product details</b>	
product component	
• trip indicator	No
• auxiliary switch	No
• voltage trigger	No
• undervoltage release	No
• undervoltage release with leading contact	No
product extension / optional / motor drive	Yes
<b>Product function</b>	
product function	
• of thermal overload trip unit	fixed
• grounding protection	No
• for neutral conductors / short-circuit and overload proof	No
• overload protection	Yes
<b>Short circuit</b>	
breaking capacity operating short-circuit current (Ics)	
• at 240 V / rated value	65 kA
• at 415 V / rated value	55 kA
• at 500 V / rated value	14 kA
• at 690 V / rated value	4 kA
breaking capacity maximum short-circuit current (Icu)	
• at 240 V / rated value	65 kA
• at 415 V / rated value	55 kA
• at 440 V / rated value	25 kA
• at 480 V / acc. to NEMA / rated value	25 kA
• at 500 V / rated value	18 kA
• at 600 V / acc. to NEMA / rated value	8 kA
• at 690 V / rated value	8 kA
<b>Connections</b>	
arrangement of electrical connectors / for main current circuit	front side
type of connectable conductor cross-sections / for main contacts	
• with flexible busbar	12 x 10 mm
• solid	2.5 ... 95 mm <sup>2</sup>
• finely stranded / with core end processing	2.5 ... 50 mm <sup>2</sup>
• stranded	2.5 ... 95 mm <sup>2</sup>
type of connectable conductor cross-sections / for auxiliary contacts	
• solid	0.75 ... 1.5 mm <sup>2</sup>
• finely stranded / with core end processing	0,75 ... 1.0 mm <sup>2</sup>
type of electrical connection / for main current circuit	box terminal
<b>Mechanical Design</b>	
height	157.5 mm
width	104.5 mm
depth	106.5 mm
fastening method	fixed mounting

## Environmental conditions

ambient temperature / during operation	
• minimum	0 °C
• maximum	70 °C
ambient temperature / during storage	
• minimum	-40 °C
• maximum	80 °C

## General Product Approval

EMC



[Miscellaneous](#)

[TSE](#)

[KC](#)



## Declaration of Conformity

### Test Certificates

### Marine / Shipping



EG-Konf.

[Special Test Certificate](#)



ABS



BUREAU  
VERITAS



LRS



PRS

## Marine / Shipping

## other



RINA



RMRS



DNV-GL

[Miscellaneous](#)

[Confirmation](#)

[Environmental Confirmations](#)

## other

[Miscellaneous](#)

## Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=3VL1706-1DA33-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VL1706-1DA33-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mfb=3VL1706-1DA33-0AA0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=3VL1706-1DA33-0AA0)

CAx-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

