



Polypropylene Flexible Conduit Range

Polypropylene Flexible Conduit



NC20/10MCP

Ref No	Description
N20/50M*	50 metre x 20mm Conduit - Black
N25/50M*	50 metre x 25mm Conduit - Black
N32/50M*	50 metre x 32mm Conduit - Black
N20/50MW	50 metre x 20mm Conduit - White
N25/50MW	50 metre x 25mm Conduit - White
N32/50MW	50 metre x 32mm Conduit - White
N20G	20mm Standard Gland, c/w Lock Nut - Black
N25G	25mm Standard Gland, c/w Lock Nut - Black
N32G	32mm Standard Gland, c/w Lock Nut - Black
N20GW	20mm Standard Gland, c/w Lock Nut - White
N32GW	32mm Standard Gland, c/w Lock Nut - White

* Complies to BS 4607 & tested to 460V

Contractor Packs (Polypropylene)

- Complies with BS 4607
- Polypropylene conduit temperature range 0-95 Deg C
- IP51 ingress protection
- Low smoke and fume, self extinguishing. UV stabilised.

Ref No	Description
N20/10MCP	10 metre x 20mm Conduit, c/w 10 Glands - Black
N25/10MCP	10 metre x 25mm Conduit, c/w 10 Glands - Black
N20/10MCPW	10 metre x 20mm Conduit, c/w 10 Glands - White
N25/10MCPW	10 metre x 25mm Conduit, c/w 10 Glands - White



N20G



NC20/50M



NC20/10MCPW